


B-Safe® Ball Valve Lockout

LCK119 For 1cm to 3.2cm Valves w/ Handles up to 19cm L, 1 each

Ball valve lock installs in seconds to cover handle and prevent unauthorised use

- Installs in seconds to completely cover handles and prevent unauthorised use
- Highly-visible, fully-dielectric polypropylene resists chemicals, cracking, abrasion, rust and extreme temperatures
- Accepts handles up to 2.5cm wide
- Fits 1cm to 3.2cm valves with handles up to 19cm long and locks in open position on pipes up to 3.8cm diameter
- Helps you meet regs regarding lockout/tagout procedures
- This simple lockout/tagout solution will help your facility meet life-saving regulations

Use With	1cm to 3.2cm Valves w/ Handles up to 19cm L
Colour	Bright Red
Temperature Limit	-46°C (-50°F) to 183°C (360°F)
Sold as	1 each
Weight	0.18 kg
Composition	Polypropylene

Technical Documents

The Provision and Use of Work Regulations 1998, Regulation 22

New Pig
World's best stuff for leaks, drips and spills.

Hogs Hill • Watt Place • Hamilton International Technology Park • Blantyre • Glasgow • G72 0AH
0800 919 900 • newpig.co.uk • pigpen@newpig.com