

## Corner for PIG® SpillBlocker® Dike

PLR268 12cm x 13cm x 7.6cm, 100%  
Polyurethane, 1 each



Turn the corner with your SpillBlocker Dikes using this leakproof 90-degree connector.

- Add this handy corner piece to a pair of SpillBlocker Dikes to create a 90° angle
- Built-in dovetail connectors form a liquid-proof seal
- Build any shape or configuration to suit your application or environment



Item#	Description	Dimensions	Weight
PLR268-BK	Black	12cm W x 13cm L x 7.6cm H	.91 kg

Item#	Description	Dimensions	Weight
PLR268-BK	Black		

<b>Style</b>	Non-Weight Bearing
<b>Dimensions</b>	12cm W x 13cm L x 7.6cm H
<b>Intended For</b>	Use on Smooth Surface
<b>Max liquid temp exposure</b>	Max Exposure Limit 107°C (225°F) for up to 30 Minutes
<b>Storage Temp Range</b>	Store from -18°C (0°F) to 49°C (120°F)
<b>Temperature Limit</b>	Works from -18°C (0°F) to 71°C (160°F) up to 12 months
<b>Sold as</b>	1 each
<b>Weight</b>	.91 kg
<b>New Pig Patent</b>	5,236,281
<b>Composition</b>	100% Polyurethane

### Technical Documents

[PIG SpillBlocker Dikes, DrainBlocker Drain Covers and other Blockers](#)

[Technical Data Sheet for PIG® Blocker Products](#)

### Disclaimers

## Urethane Notice

Due to the nature of softer urethane, the physical properties of these products may change over time with exposure to certain environmental conditions like temperature, humidity and UV radiation. Typical life expectancy is 5 years. Please inspect the stored product regularly to ensure it is in a usable state. For optimum performance, ensure that the area where the product will be deployed is free of debris, cracks and holes. For more details and for chemical compatibility, please call Technical Services.



Hogs Hill • Watt Place • Hamilton International Technology Park • Blantyre • Glasgow • G72 0AH  
0800 919 900 • [newpig.co.uk](http://newpig.co.uk) • [pigpen@newpig.com](mailto:pigpen@newpig.com)