

Drop-Ceiling Leak Diversion System

TLS367 61cm x 122cm

Leak diversion system replaces damaged ceiling tile for discrete channeling of liquids until you find and fix the leak.

- Remove damaged tile and replace it with a leak diversion system panel to channel away liquids
- minimises wet floors, damaged equipment and disturbances to workers
- Captures leaks and drips and diverts them to a drain or storage tank with the included hose
- Includes drain hose and clips to secure hose to ceiling grids
- Flow rate of 3.8-litres per minute when used with included hose
- After leak has been repaired, simply uninstall and store for later use
- Replaces any standard 61cm x 122cm drop ceiling tile



Specifications

Use With	Drop Ceilings
Drainage Hose	Included
Hanging Straps	N/A
Corner Style	N/A
Additional Grommets per Side	N/A
Total Grommets/D-Rings	N/A
Installation Method	Frame
Style	Rectangle
Colour	White
Dimensions	61cm W x 122cm L
Hose Connector	.5"
Sold as	1 each
Weight	3.6 kg
# per Pallet	40
Composition	Ceiling Diverter - Polystyrene; Hose - PVC; Pipe Connector - Polypropylene;

	Plastic Clips - Polypropylene; Ties - Polyamide
Flow Rate	0.76 ltr. per minute
Includes	1 - 61cm x 122cm Drop-Ceiling Panel 1 - 7.6m L Hose 6 - Ceiling Clips 9 - Tie Wraps

Technical Documents

PIG Drop-Ceiling Leak Diversion System

Disclaimers

Maximum Working Temperature

Not suitable for temperatures over 170°F/77°C.



Hogs Hill • Watt Place • Hamilton International Technology Park • Blantyre • Glasgow • G72 0AH
0800 919 900 • newpig.co.uk • pigpen@newpig.com