

Dual-Purpose Storage Unit

GENE226 300cm x 165cm x 320cm, Holds (16)
210 ltr. Drums or (4) IBCs

Secure Steel Storage Unit has the capacity for both drums and IBCs. 22cm deep sump exceeds containment capacity requirements.

- Storage Unit is designed to protect the environment and personnel by capturing Drum or IBC leaks and spills before they can reach the ground
- Large sump capacity helps you meet Oil Storage Regulations
- 22cm deep leakproof sump catches leaks, drips and spills; helps prevent groundwater contamination
- Per HSG 51, light weight roof is designed to be the weakest point to maximise safety; in case of fire or explosion, the blast will go upwards through the roof instead of blowing the doors or walls outwards
- Fully-welded, 2mm-thick steel construction offers improved strength and durability over riveted units; ideal for flammable storage
- Sliding doors allow easy forklift access for loading and unloading Drums or IBCs; lockable and attached to frame at both the top and the bottom for added security
- High- and low-level flame-arrested vents increase air circulation and help prevent pressure buildup
- Galvanised roof with 8cm wide guttering at the rear is pitched to prevent the accumulation of rainwater
- Manufactured with welded cross member support bars on both storage levels, suitable for pallet storage
- Empty unit can be moved with a forklift or crane
- Chemical- and corrosion-resistant paint also withstands harsh outdoor conditions; minimum of 100 microns thick



GENE226-YW	Yellow	300cm W x 165cm D x 320cm H	920 kg
GENE226-RD	Red	300cm W x 165cm D x 320cm H	920 kg
GENE226-GR	Green	300cm W x 165cm D x 320cm H	920 kg
GENE226-BL	Blue	300cm W x 165cm D x 320cm H	920 kg

Item#	Description	Dimensions	Weight
GENE226-YW	Yellow		
GENE226-RD	Red		
GENE226-GR	Green		
GENE226-BL	Blue		

Dimensions	300cm W x 165cm D x 320cm H
Load Capacity UDL	6000 kg
Sump Capacity	1125 L
Rain Gutter	8cm Gutter on Rear Only
Sold as	1 each
Weight	920 kg
Composition	2mm profiled mild sheet steel over 100mm x 50mm x 3mm RHS tube
Capacity	(16) 210 ltr. Drums or (4) IBCs
Door Style	Sliding Doors

Technical Documents

HS(G) 51

[The Control of Pollution \(Oil Storage\) Regulations \(Northern Ireland\) 2010](#)

[The Control of Pollution \(Oil Storage\)\(England\) Regulations 2001](#)

[The Water Environment \(Oil Storage\) \(Scotland\) Regulations 2006](#)

[The Water Resources \(Control of Pollution\) \(Oil Storage\) \(Wales\) Regulations 2016](#)



Hogs Hill • Watt Place • Hamilton International Technology Park • Blantyre • Glasgow • G72 0AH
 0800 919 900 • newpig.co.uk • pigpen@newpig.com

