

**Sorry,
no picture
available**

Dual-Purpose Storage Unit

GENE229 590cm x 330cm x 320cm, Holds (64)
210 ltr. Drums or (16) IBCs

Secure Steel Storage Unit has the capacity for both drums and IBCs. 22cm deep sump exceeds containment capacity requirements.

- Storage Unit is designed to protect the environment and personnel by capturing Drum or IBC leaks and spills before they can reach the ground
- Large sump capacity helps you meet Oil Storage Regulations
- 22cm deep leakproof sump catches leaks, drips and spills; helps prevent groundwater contamination
- Per HSG 51, light weight roof is designed to be the weakest point to maximise safety; in case of fire or explosion, the blast will go upwards through the roof instead of blowing the doors or walls outwards
- Fully-welded, 2mm-thick steel construction offers improved strength and durability over riveted units; ideal for flammable storage
- Sliding doors on two sides allow easy forklift access for loading and unloading Drums or IBCs; lockable and attached to frame at both the top and the bottom for added security
- High- and low-level flame-arrested vents increase air circulation and help prevent pressure buildup
- Galvanised roof with 8cm wide guttering at the front and rear is pitched to prevent the accumulation of rainwater
- Manufactured with welded cross member support bars on both storage levels, suitable for pallet storage
- Empty unit can be moved with a forklift or crane
- Chemical- and corrosion-resistant paint also withstands harsh outdoor conditions; minimum of 100 microns thick

| | | | |
|------------|--------|-----------------------------|---------|
| GENE229-YW | Yellow | 590cm W x 330cm D x 320cm H | 3390 kg |
| GENE229-RD | Red | 590cm W x 330cm D x 320cm H | 3390 kg |
| GENE229-GR | Green | 590cm W x 330cm D x 320cm H | 3390 kg |
| GENE229-BL | Blue | 590cm W x 330cm D x 320cm H | 3390 kg |

| Item# | Description | Dimensions | Weight |
|------------|-------------|------------|--------|
| GENE229-YW | Yellow | | |
| GENE229-RD | Red | | |
| GENE229-GR | Green | | |
| GENE229-BL | Blue | | |

| | |
|--------------------------|--|
| Dimensions | 590cm W x 330cm D x 320cm H |
| Load Capacity UDL | 24000 kg |
| Sump Capacity | 4000 L |
| Rain Gutter | 8cm Gutter on Front & Rear |
| Sold as | 1 each |
| Weight | 3390 kg |
| Composition | 2mm profiled mild sheet steel over 100mm x 50mm x 3mm RHS tube |
| Capacity | (64) 210 ltr. Drums or (16) IBCs |
| Door Style | Sliding Doors |

Technical Documents

HS(G) 51

[The Control of Pollution \(Oil Storage\) Regulations \(Northern Ireland\) 2010](#)

[The Control of Pollution \(Oil Storage\)\(England\) Regulations 2001](#)

[The Water Environment \(Oil Storage\) \(Scotland\) Regulations 2006](#)

[The Water Resources \(Control of Pollution\) \(Oil Storage\) \(Wales\) Regulations 2016](#)



Hogs Hill • Watt Place • Hamilton International Technology Park • Blantyre • Glasgow • G72 0AH
 0800 919 900 • newpig.co.uk • pigpen@newpig.com

