

## Dual-Purpose Storage Unit

GENE230 890cm x 330cm x 320cm, Holds (96)  
210 ltr. Drums or (24) IBCs



Secure Steel Storage Unit has the capacity for both drums and IBCs. 22cm deep sump exceeds containment capacity requirements.

- Storage Unit is designed to protect the environment and personnel by capturing Drum or IBC leaks and spills before they can reach the ground
- Large sump capacity helps you meet Oil Storage Regulations
- 22cm deep leakproof sump catches leaks, drips and spills; helps prevent groundwater contamination
- Per HSG 51, light weight roof is designed to be the weakest point to maximise safety; in case of fire or explosion, the blast will go upwards through the roof instead of blowing the doors or walls outwards
- Fully-welded, 2mm-thick steel construction offers improved strength and durability over riveted units; ideal for flammable storage
- Sliding doors on two sides allow easy forklift access for loading and unloading Drums or IBCs; lockable and attached to frame at both the top and the bottom for added security
- High- and low-level flame-arrested vents increase air circulation and help prevent pressure buildup
- Galvanised roof with 8cm wide guttering at the front and rear is pitched to prevent the accumulation of rainwater
- Manufactured with welded cross member support bars on both storage levels, suitable for pallet storage
- Empty unit can be moved with a forklift or crane
- Chemical- and corrosion-resistant paint also withstands harsh outdoor conditions; minimum of 100 microns thick

Item#	Description	Dimensions	Weight
GENE230-YW	Yellow	890cm W x 330cm D x 320cm H	5100 kg
GENE230-RD	Red	890cm W x 330cm D x 320cm H	5100 kg
GENE230-GR	Green	890cm W x 330cm D x 320cm H	5100 kg

GENE230-BL	Blue	890cm W x 330cm D x 320cm H	5100 kg
------------	------	-----------------------------	---------

## Metric Equivalent:

Item#	Description	Dimensions	Weight
GENE230-YW	Yellow		
GENE230-RD	Red		
GENE230-GR	Green		
GENE230-BL	Blue		

## Specifications

Dimensions	890cm W x 330cm D x 320cm H
Load Capacity UDL	36000 kg
Sump Capacity	6000 L
Rain Gutter	8cm Gutter on Front & Rear
Sold as	1 each
Weight	5100 kg
Composition	2mm profiled mild sheet steel over 100mm x 50mm x 3mm RHS tube
Capacity	(96) 210 ltr. Drums or (24) IBCs
Door Style	Sliding Doors

## Technical Documents

HS(G) 51

[The Control of Pollution \(Oil Storage\) Regulations \(Northern Ireland\) 2010](#)

[The Control of Pollution \(Oil Storage\)\(England\) Regulations 2001](#)

[The Water Environment \(Oil Storage\) \(Scotland\) Regulations 2006](#)

[The Water Resources \(Control of Pollution\) \(Oil Storage\) \(Wales\) Regulations 2016](#)



**New Pig**

World's best stuff for leaks, drips and spills.

Hogs Hill • Watt Place • Hamilton International Technology Park • Blantyre • Glasgow • G72 0AH  
0800 919 900 • [newpig.co.uk](http://newpig.co.uk) • [pigpen@newpig.com](mailto:pigpen@newpig.com)