

Dual-Purpose Storage Unit

GENE230 890cm x 330cm x 320cm, Holds (96) 210 ltr. Drums or (24) IBCs

Secure Steel Storage Unit has the capacity for both drums and IBCs. 22cm deep sump exceeds containment capacity requirements.

– Storage Unit is designed to protect the environment and personnel by capturing Drum or IBC leaks and spills before they can reach the ground
– Large sump capacity helps you meet Oil Storage Regulations
– 22cm deep leakproof sump catches leaks, drips and spills; helps prevent groundwater contamination
– Per HSG 51, light weight roof is designed to be the weakest point to maximise safety; in case of fire or explosion, the blast will go upwards through the roof instead of blowing the doors or walls outwards
– Fully-welded, 2mm-thick steel construction offers improved strength and durability over riveted units; ideal for flammable storage
– Sliding doors on two sides allow easy forklift access for loading and unloading Drums or IBCs; lockable and attached to frame at both the top and the bottom for added security
– High- and low-level flame-arrested vents increase air circulation and help prevent pressure buildup
– Galvanised roof with 8cm wide guttering at the front and rear is pitched to prevent the accumulation of rainwater
– Manufactured with welded cross member support bars on both storage levels, suitable for pallet storage
– Empty unit can be moved with a forklift or crane
– Chemical- and corrosion-resistant paint also withstands harsh outdoor conditions; minimum of 100 microns thick

Item#	Description	Dimensions	Weight

GENE230-YW	Yellow	890cm W x 330cm D x 320cm H	5100 kg
GENE230-RD	Red	890cm W x 330cm D x 320cm H	5100 kg
GENE230-GR	Green	890cm W x 330cm D x 320cm H	5100 kg
GENE230-BL	Blue	890cm W x 330cm D x 320cm H	5100 kg

Item#	Description	Dimensions	Weight
GENE230-YW	Yellow		
GENE230-RD	Red		
GENE230-GR	Green		
GENE230-BL	Blue		

Dimensions	890cm W x 330cm D x 320cm H
Load Capacity UDL	36000 kg
Sump Capacity	6000 L
Rain Gutter	8cm Gutter on Front & Rear
Sold as	1 each
Weight	5100 kg
Composition	2mm profiled mild sheet steel over 100mm x 50mm x 3mm RHS tube
Capacity	(96) 210 ltr. Drums or (24) IBCs
Door Style	Sliding Doors

Technical Documents

HS(G) 51

The Control of Pollution (Oil Storage) Regulations (Northern Ireland) 2010

The Control of Pollution (Oil Storage)(England) Regulations 2001

The Water Environment (Oil Storage) (Scotland) Regulations 2006

The Water Resources (Control of Pollution) (Oil Storage) (Wales) Regulations 2016