

External Drum Store for 25ltr Drums

GENE260 Holds (48) 25 ltr. Steel or Poly Drums, 380 L Sump Capacity, 1500 kg Load Capacity

High capacity cabinet holds up to 48 25-litre drums on three separate levels.

- Padlockable sliding doors for added security (padlock not included)
- Fully welded, leakproof sump catches leaks, drips and spills; helps prevent groundwater contamination
- Two fixed, perforated galvanised steel shelves and galvanised grid flooring; flooring removes easily for sump inspection and cleaning
- Vents located on upper and lower half of cabinet encourage air circulation within the cabinet
- Fully-welded, 2mm-thick steel construction offers improved strength and durability over riveted units; ideal storing flammables, chemicals and hazardous materials
- 500kg UDL weight capacity per level
- Per HSG 51, light weight roof is designed to be the weakest point to maximise safety; in case of fire or explosion, the blast will go upwards through the roof instead of blowing the doors or walls outwards
- Chemical- and corrosion-resistant RAL3020 Red paint withstands harsh outdoor conditions; minimum of 100 microns thick

Specifications

Colour	Red
Dimensions	80cm W x 250cm L x 240cm H
Load Capacity UDL	1500 kg
Sump Capacity	380 L
Double-Stackable Unit	Not Double-Stackable
Drain	No Drain
Fork Truck Access	Two-Way Fork Access, Can Move Loaded
Grates	(2) 63cm L x 125cm W Grates
Sold as	1 each
Weight	600 kg
Composition	2mm Mild sheet steel fully welded construction over 50mm x 50mm x 3mm RHS tube
Capacity	(48) 25 ltr. Steel or Poly Drums



Technical Documents

HS(G) 51

The Control of Pollution (Oil Storage) Regulations (Northern Ireland) 2010

The Control of Pollution (Oil Storage)(England) Regulations 2001

The Water Environment (Oil Storage) (Scotland) Regulations 2006

The Water Resources (Control of Pollution) (Oil Storage) (Wales) Regulations 2016



New Pig

World's best stuff for leaks, drips and spills.

Hogs Hill • Watt Place • Hamilton International Technology Park • Blantyre • Glasgow • G72 0AH

0800 919 900 • newpig.co.uk • pigpen@newpig.com