

Non-Skid Step Tape

FLM642 15cm x 18m

Durable epoxy-coated grit helps create safe footing anywhere.

- Durable mineral grit compound creates a non-skid surface for safe footing throughout your facility
- Grit is sealed with 2-part epoxy resin for durability and to prevent shedding
- Resists oil, water and heavy foot traffic for long service life
- Adhesive features low initial tack for minutes of easy repositioning
- Tape removes without residue
- Just cut to length, remove protective backing and apply



Item#	Description	Dimensions	Weight
FLM642-SY	Safety Yellow	15cm W x 18m L	2.5 kg
FLM642-BK	Black	15cm W x 18m L	2.5 kg

Metric Equivalent:

Item#	Description	Dimensions	Weight
FLM642-SY	Safety Yellow		
FLM642-BK	Black		

Specifications

Dimensions	15cm W x 18m L
Installation Temperature	16°C (60°F) Minimum Air, 10°C (50°F) Minimum Surface
Temperature Limit	-25°C (-14°F) to 65°C (150°F)
Sold as	1 roll
Weight	2.5 kg
Composition	Mineral Abrasive Compound
Thickness	30 mil Black, 25 mil Hazard & Yellow

Technical Documents

The Disability Discrimination Act 1995, Part III