

OilSafe® Standard Pump

GLE0008 For Oil Based Liquids, 1 ltr./14 Strokes, Fits Oil Safe® Drums

This high volume, down-stroke discharge pump is perfect to complete your OilSafe® system.

- Dispenses lubricants in hard-to-reach spots
- Dispensing is clean and easy with removable 152cm hose with hook outlet anti-drip nozzle
- Delivers 1 litre for approximately 12-14 strokes and handles up to ISO 460 viscosity fluids in normal operating temperatures
- Aluminium anti-drip nozzle fits 1/2" and larger filler holes
- Coiled wire inside hose prevents kinking
- Design screws easily into Oil Safe® Utility Lid (sold separately)
- Utility Lid (GLE0017) is required to attach Pump to 3-, 5- and 10-Litre Oil Safe® Containers (GLE0002, GLE0003 and GLE0004)

Use With	Oil Based Liquids
Outlet	1520mm Hose
Style	Piston Operated
Colour	Black & Silver
Sold as	1 each
Weight	.86 kg
Composition	Hose - PVC; Nozzle - Aluminium; Extension sleeve - HDPE; Shaft - Mild steel; Body - Nylon polyamide PA6; Cylinder - Zinc plated mild steel; Seal - Nitrile (Buna N)
Fits	Oil Safe® Drums
Maximum Flow Rate	1 ltr./14 Strokes
Maximum Viscosity	SAE 85W-140 Oil