

## **PIG®** Conical Drain Plug

PLR208 For 5cm Dia. Drains, 1 each

Ideal for plugging the outflow on long channel and trench-style drains.

- Durable polyurethane plug forms a liquid-tight, chemical-resistant seal in seconds
- Simply wedge plug in drain outflow pipe
- Installed plug is low-profile enough to fit below floor grate
- Allows your drain to function normally when plug is not in place; removes easily



## pig

## **Specifications**

Use With	5cm Dia. Drains
Colour	Yellow
Dimensions	ext. dia. 6.4cm x 13cm H
Sold as	1 each
Weight	.6 kg
Composition	Polyurethane with metal eye bolt
UV Resistant	Not UV Resistant

## **Technical Documents**

- PIG SpillBlocker Dikes, DrainBlocker Drain Covers and other Blockers
- Technical Data Sheet for PIG® Blocker Products
- **Environmental Protection Act 1990**
- Water Resources Act 1991
- Disclaimers
- Urethane Notice

Due to the nature of softer urethane, the physical properties of these products may change over time with exposure to certain environmental conditions like temperature, humidity and UV radiation. Typical life expectancy is 5 years. Please inspect the stored product regularly to ensure it is in a usable state. For optimum performance, ensure that the area where the product will be deployed is free of debris, cracks and holes. For more details and for chemical compatibility, please call Technical Services.



World's best stuff for leaks, drips and spills.

Hogs Hill • Watt Place • Hamilton International Technology Park • Blantyre • Glasgow • G72 0AH 0800 919 900 • newpig.co.uk • pigpen@newpig.com