

## PIG® DrainBlocker® Drain Cover

PLR412 For Round Drains up to 15cm Dia., 1 each

Protect your drains with the patented design that seals tight and won't rip.

- Patented two-layer design seals tight to protect drains and won't rip
- Use cover for quick spill response or long-term, outdoor deployment without worrying about degradation
- Vinyl composite top layer resists stretching, ripping and tearing
- Elvaloy technology provides lifelong flexibility plus chemical, UV and infrared light resistance to vinyl top
- Super-sealing urethane bottom layer conforms to uneven surfaces and tightly seals drain openings to block liquid
- Cover withstands prolonged exposure to diesel fuel and petrol, even when completely submerged
- Ideal for drain protection where liquid transfers, washdowns or other leak- and spill-prone jobs are common
- Eliminates the need to frequently deploy and remove a temporary cover or permanently seal your drains
- High-visibility yellow top layer draws attention to spills for increased safety
- Note: Elvaloy top can become slippery when wet. Please use caution.



<b>Use With</b>	Round Drains up to 15cm Dia.
<b>Style</b>	Walk-on
<b>Colour</b>	Yellow & Black
<b>Dimensions</b>	ext. dia. 30.5cm x .8cm H
<b>Intended For</b>	Use on Smooth Surface
<b>Max liquid temp exposure</b>	Max Exposure Limit 107°C (225°F) for up to 30 Minutes
<b>Storage Temp Range</b>	Store from -18°C (0°F) to 49°C (120°F)
<b>Temperature Limit</b>	Works from -18°C (0°F) to 71°C (160°F) up to 12 months

<b>Sold as</b>	1 each
<b>Weight</b>	1.4 kg
<b>New Pig Patent</b>	8,117,686
<b># per Pallet</b>	360
<b>Composition</b>	Top - Elvaloy Vinyl; Bottom - Urethane
<b>UV Resistant</b>	UV Resistant

## Technical Documents

[PIG DrainBlocker Drain Cover with DuPont Elvaloy](#)

[Technical Data Sheet for PIG® Blocker Products](#)

[Environmental Protection Act 1990](#)

[Water Resources Act 1991](#)

## Disclaimers

### Urethane Notice

Due to the nature of softer urethane, the physical properties of these products may change over time with exposure to certain environmental conditions like temperature, humidity and UV radiation. Typical life expectancy is 5 years. Please inspect the stored product regularly to ensure it is in a usable state. For optimum performance, ensure that the area where the product will be deployed is free of debris, cracks and holes. For more details and for chemical compatibility, please call Technical Services.



Hogs Hill • Watt Place • Hamilton International Technology Park • Blantyre • Glasgow • G72 0AH  
0800 919 900 • [newpig.co.uk](http://newpig.co.uk) • [pigpen@newpig.com](mailto:pigpen@newpig.com)