





PLR304 For Square Drains up to 91cm, 1 each

The toughest drain cover you can buy is the only one that can handle drive-overs - even from heavy tankers. Go ahead and drive over it!

- Patented design is the only cover tough enough to handle drive-overs - even from heavy tankers. Only from New Pig
- Ideal for long-term drain protection where liquid transfers, washdowns or other leak- and spillprone jobs are common
- Eliminates the need to frequently deploy and remove a temporary cover or permanently seal your drains
- Tough, patented-rubber HogHyde Skin stands up to punctures, tearing and abrasion, even under heavy vehicle traffic from tankers, trucks or forklifts
- Super-sealing urethane bottom layer conforms to uneven surfaces and tightly seals drain openings to block liquid
- Also withstands UV rays, infrared light and all weather conditions; keep outdoors as long as needed without worrying about degradation
- Polyurethane and rubber materials resist water, oils and many chemicals
- Leave down as preventive measure or store for emergency response
- Includes a nylon storage bag for easy transportation and fast spill response
- Need a custom size? Call Tel 0800 919 900





## **Specifications**

Use With	Square Drains up to 91cm
Style	Drive-over
Colour	Top - Black; Bottom - Blue
Dimensions	107cm W x 107cm L x 1cm H
Intended For	Use on Smooth Surface
Max liquid temp exposure	Max Exposure Limit 107°C (225°F) for up to 30 Minutes
Storage Temp Range	Store from -18°C (0°F) to 49°C (120°F)
Temperature Limit	Works from -18°C (0°F) to 71°C (160°F) up to 12 months

Sold as	1 each
Weight	12.7 kg
New Pig Patent	8,117,686
# per Pallet	25
Composition	Top:Rubber; Bottom: Urethane
Includes	1 - PIG® Drive-Over DrainBlocker® Drain Cover 1 - Nylon Storage Bag
UV Resistant	UV Resistant

## **Technical Documents**

PIG Drive-Over DrainBlocker Drain Cover

Urethane Use, Care and Storage

**PIG Blocker Products** 

**Environmental Protection Act 1990** 

Water Resources Act 1991

## **Disclaimers**

## **Urethane Notice**

Due to the nature of softer urethane, the physical properties of these products may change over time with exposure to certain environmental conditions like temperature, humidity and UV radiation. Typical life expectancy is 5 years. Please inspect the stored product regularly to ensure it is in a usable state. For more details and for chemical compatibility, please call Technical Services.



Hogs Hill • Watt Place • Hamilton International Technology Park • Blantyre • Glasgow • G72 0AH 0800 919 900 • newpig.co.uk • pigpen@newpig.com