
PIG® Drive-Over SpillBlocker™ Dike Corner

PLR951 5cm x 15cm x 2.5cm, Top - Co-Polymer Geomembrane; Bottom - Polyurethane, 1 each







Turn the corner with your Drive-Over SpillBlocker Dikes using this leak-proof 90-degree connector.

– Adapt to obstacles and create square or rectangular perimeters based on the needs of your exact containment space with this 90-degree corner
– Maintain a solid, leak-proof drive-over containment berm when you use this connector designed to fit perfectly with your Drive-Over SpillBlocker Dikes
– Trust this corner piece to hold strong without compromise—even when driving over it—since it's made of the same super-tough HogHyde® and other materials as the rest of your barrier

Style	Drive-over
Colour	Grey
Dimensions	5cm W x 15cm L x 2.5cm H
Intended For	Use on Smooth Surface
Max liquid temp exposure	Max Exposure Limit 107°C (225°F) for up to 30 Minutes
Storage Temp Range	Store from -18°C (0°F) to 49°C (120°F)
Temperature Limit	Works from -18°C (0°F) to 71°C (160°F) up to 12 months
Sold as	1 each
Weight	.5 kg
# per Pallet	462
Composition	Top - Co-Polymer Geomembrane; Bottom - Polyurethane

Technical Documents

Urethane Use, Care and Storage

Technical Data Sheet for PIG® Blocker Products

Disclaimers

Urethane Notice

Due to the nature of softer urethane, the physical properties of these products may change over time with exposure to certain environmental conditions like temperature, humidity and UV radiation. Typical life expectancy is 5 years. Please inspect the stored product regularly to ensure it is in a usable state. For optimum performance, ensure that the area where the product will be deployed is free of debris, cracks and holes. For more details and for chemical compatibility, please call Technical Services.

New Pig
World's best stuff for leaks, drips and spills.

Hogs Hill • Watt Place • Hamilton International Technology Park • Blantyre • Glasgow • G72 0AH
0800 919 900 • newpig.co.uk • pigpen@newpig.com