

PIG® Drive-Over SpillBlocker® Dike

PLR350 5cm x 305cm x 2.5cm, Top - EPDM Bottom - Urethane, 1 each

Divert stormwater or create a liquid-proof perimeter with the ONLY flexible barrier designed for longterm outdoor use.

- First flexible barrier designed for long-term outdoor use; even when driven over, dike won't crush or compromise containment
- Contains leaks and diverts stormwater help you meet stormwater regs
- HogHyde skin stands up to heavy traffic driveovers and resists UV rays
- Super-sealing urethane bonds to concrete and smooth surfaces without adhesives
- Molds easily around mounting brackets or other obstacles
- Narrow footprint fits tight ledges and small surface areas
- Provides a full-width bond that strengthens over time
- Reusable dike cleans up with soap and water
- Pick up and reposition as needed



Specifications

Style	Drive-over
Colour	Black
Dimensions	5cm W x 305cm L x 2.5cm H
Intended For	Use on Smooth Surface
Max liquid temp exposure	Max Exposure Limit 107°C (225°F) for up to 30 Minutes
Storage Temp Range	Store from -18°C (0°F) to 49°C (120°F)
Temperature Limit	Works from -18°C (0°F) to 71°C (160°F) up to 12 months
Sold as	1 each
Weight	5.9 kg
New Pig Patent	5,236,281 and Patents Pending
# per Pallet	108
Composition	Top - EPDM Bottom - Urethane

Technical Documents

PIG Drive-Over DrainBlocker Drain Cover

Urethane Use, Care and Storage

Instructions for PIG® Drive-Over SpillBlocker® Dike

PIG Blocker Products

Disclaimers

Urethane Notice

Due to the nature of softer urethane, the physical properties of these products may change over time with exposure to certain environmental conditions like temperature, humidity and UV radiation. Typical life expectancy is 5 years. Please inspect the stored product regularly to ensure it is in a usable state. For more details and for chemical compatibility, please call Technical Services.



Hogs Hill • Watt Place • Hamilton International Technology Park • Blantyre • Glasgow • G72 0AH 0800 919 900 • newpig.co.uk • pigpen@newpig.com