








PIG® Frameless Storm Drain Filter

FLT116 Filters Oil; Sediment; Trash; Debris; Floatables, For Storm Drains 51cm to 76cm W & 51cm to 91cm L; Round Drains 51cm to 76cm Dia., 91cm x 107cm x 43cm

New and improved ""witches hat"" drain guard design! Catch basin insert protects drains of all sizes in high-traffic areas with better filtering of oil, sediment, debris and trash from stormwater runoff.

- New! Redesigned for better filtration, improved handling and all-around performance
- Frameless design is ideal for small drains of any shape, even shallow drains
- Heavy-duty, hi-viz strap allows easier handling and removal
- Four-stage filtration process treats more water and removes more oil than basic storm drain filters
- Overflow ports help prevent blockage during high water flow
- Fits circular drain sizes 51cm to 76cm in diameter
- Fits irregular, rectangular and square drain sizes 51cm to 76cm width to 51cm to 91cm length
- Trim product to allow 7-8cm of material to extend above grate
- Pore size is 0.074 mm, 74 microns, 0.0029 inches or 200 sieve

Use With	Storm Drains 51cm to 76cm W & 51cm to 91cm L; Round Drains 51cm to 76cm Dia.
Colour	Black
Dimensions	91cm W x 107cm L x 43cm H
Absorbency	Up to 4.9 L
Load Capacity	18kg
Installation	Installs below grate
Sold as	1 each
Weight	.7 kg

New Pig Patent	10,508,430
# per Pallet	99
Composition	Insert Strips and Ring: Polyester; Straps: Polyester
Filters	Oil; Sediment; Trash; Debris; Floatables
Maximum Flow Rate	1,514 ltr./Minute

Technical Documents

Instructions for Frameless Storm Drain Filter

Product Performance and Testing for PIG Frameless Storm Drain Filter (Medium)

Environmental Protection Act 1990

The Control of Pollution Act (1974)

Water Resources Act 1991

New Pig
World's best stuff for leaks, drips and spills.

Hogs Hill • Watt Place • Hamilton International Technology Park • Blantyre • Glasgow • G72 0AH
0800 919 900 • newpig.co.uk • pigpen@newpig.com