

PIG® Grippy® Adhesive-Backed Absorbent Mat

MAT3251 81cm x 102cm, Absorbs up to 1.3 L

Our exclusive, adhesive-backed mat stays put to catch drips from vehicles or industrial equipment — and it won't blow away when the door is open.

- Adhesive-backed absorbent mat stays exactly where you put it with no shifting or bunching up underfoot
- Fits perfectly underneath vehicles to protect workshop floors from oily leaks and drips; reduces cleanup time to keep your workshop productive
- Proprietary adhesive sticks to the floor with a super-tight grip, but can be easily removed and repositioned so you can reuse the mat until it becomes saturated
- PIG Grippy Mat will stick to most common commercial floor surfaces, including: concrete, vinyl tile, ceramic tile, quarry tile and linoleum
- Tough, spunbond top layer with heavy-duty zigzag stitching stands up to rolling tires and service bay foot traffic
- Layers of fine-fibre polypropylene safely absorb and retains oils, coolants, water, grease, fuels, solvents, automotive fluids, paint overspray, battery acid and most other liquids
- Leakproof backing prevents absorbed liquid from soaking through to the floor
- Dark colour hides grime so the mat looks cleaner longer
- Mat ends are heat-cut for a finished, professional look
- Meets NFPA33 - Static Dissipative & OSHA Standards at conditions of 50% RH or higher
- Tested and Certified by the National Floor Safety Institute (NFSI): when used as part of your floor safety program, high-traction surfaces such as PIG Grippy Absorbent Mat have been proven to reduce slip-and-fall claims by as much as 90%



Storage Temperature	Store between 0°C - 49°C
Colour	Blue
Dimensions	81cm W x 102cm L
Mat Weight	Mediumweight
Fluids Absorbed	Oils, Coolants, Solvents & Water
Recycled Content	25% or more Recycled Content
Absorbency	Up to 1.3 L per roll
Perforated	Not Perforated
Temperature Limit	Surface temperatures from 13°C - 49°C
Sold as	1 roll
Weight	.8 kg
Composition	Absorbent - Polypropylene; Stitching - Polyester; Adhesive Backing - Proprietary Adhesive Material
Packaging	Bag
Poly-Backing	Poly-Backed
UV Resistant	Not UV Resistant

Certifications, Approvals and Ratings

NSFI Certified,ANSI B101.1- 2009

Technical Documents

- [PIG Grippy Adhesive-Backed Mat](#)
- [Storage & Shelf Life of PIG Absorbents & Absorbent Spill Kits](#)
- [Technical Data Sheet for PIG® Adhesive Backed Grippy Mat](#)
- [Instructions for PIG Grippy Absorbent Mat](#)

Disclaimers

PIG® Grippy® Absorbent Mat Notice

New Pig adhesive-backed mats are formulated to work with most common industrial and commercial floor surfaces but are not intended for home/residential use and wood flooring. All adhesive mats have some potential to leave residue or lift or discolour finish coatings, paint, and loose or pre-damaged tiles depending on the condition and age of the floor surface. If you have questions about the suitability of New Pig adhesive-backed mats for your application, test a 15 x 15cm piece in a non-critical area before use.

PIG® Grippy® Absorbent Mats should be replaced if they become saturated or show signs of wear or damage.

Customer assumes the risk that a New Pig adhesive-backed mat may damage or alter their existing flooring or floor covering. Other than warranties implied by law, New Pig provides no warranty of fitness for a particular purpose and no warranty that an

adhesive-backed mat will be fit for customer's intended use. Other than in respect of liability which New Pig cannot lawfully exclude, New Pig shall have no responsibility for, and customer hereby releases and discharges New Pig from, any direct, indirect, incidental or consequential damages to their floors, flooring material, or any other surfaces in their premises. Customer is solely responsible for determining the fitness and appropriateness of the use of New Pig adhesive-backed mats in their premises.



World's best stuff for leaks, drips and spills.

Hogs Hill • Watt Place • Hamilton International Technology Park • Blantyre • Glasgow • G72 0AH

0800 919 900 • newpig.co.uk • pigpen@newpig.com