

PIG® Grippy® Adhesive-Backed Berber Entrance Mat

GRP913X50 91cm x 15.2m, Absorbs up to 51.5 L

Keep floors safe and capture dirt and liquid at your door with our carpeted adhesive-backed runner; replace your rental rugs in entrances, walkways and lobbies with our stylish absorbent mat to prevent slips, trips and falls.

- 91cm x 15m roll allows you to create the runner or mat shape you desire to stop moisture and dirt at the door; cuts easily without fraying or unraveling so you can create the size you need
- Our stylish Berber carpeted floor mats complement modern or upscale vestibules, entryways, walkways and more
- Adhesive-backed floor mat stays exactly where you put it with no shifting, bunching up or ripples that cause slips and trips — no straightening, no hassles
- Dries out quickly without moisture soaking through to the floor; absorbs water, oil and grease and traps dirt, debris and sand to keep it from being tracked around
- Sticks to the floor with a super-tight grip, but peels up easily without leaving a residue or damaging floors
- Saves you money as a cost-effective replacement for risky and outdated traditional rubber-backed entrance mats and scraper mats that can cause slips and trips
- Commercial-grade durability allows you to keep mat in place for 3 to 6 months depending on your conditions; carpet fibres resist fading, staining and crushing
- Easy to clean: you can sweep, vacuum, mop or use your carpet extractor over Grippy Mat and it won't budge
- No rippled edges to obstruct doors or create tripping hazards; ADA compliant for wheelchairs and walkers
- Sticks to most commercial floor surfaces including concrete, VCT, linoleum, ceramic tile, quarry tile and laminate flooring
- PIG Grippy Entrance Mat is classified as slip resistance R13 according to DIN51130 suitable for use on floors in workrooms and work areas where there is an increased risk of slipping due to grease, oil, water, foods, leftovers, dust, flour, plant clippings, etc.

- Tested in accordance with BS 7976 2:2002+A1:2013, and demonstrated low slip potential in both wet and dry conditions
- Fire classification Bfl-s1 when tested according to BS EN 13501-1
- Tested and Certified by the National Floor Safety Institute (NFSI): when used as part of your floor safety program, high-traction surfaces such as PIG Grippy Entrance Mat have been proven to reduce slip-and-fall claims by as much as 90%

























Specifications

Storage Temperature	Store between 0°C - 49°C
Dimensions	91cm W x 15.2m L
Mat Weight	Mediumweight
Fluids Absorbed	Water; Grease; Oils
Recycled Content	100% Post-Consumer Recycled Polyester Fabric
Absorbency	Up to 51.5 L per roll
Perforated	Not Perforated
Temperature Limit	Surface temperatures from 13°C - 49°C
Sold as	1 roll
Weight	10.8 kg
# per Pallet	24
Composition	Absorbent - Polyester; Adhesive Backing - Proprietary Adhesive Material
Packaging	Bag
Poly-Backing	Poly-Backed
UV Resistant	Not UV Resistant

Technical Information

Certifications, Approvals and Ratings

NSFI Certified, ANSI B101.1- 2009, DIN 51130:2014 - R13, BS 7976-2:2002+A1:2103 - Low slip, BS EN 13501- 1:2007+A1:2009 - Bfl-s1, Tested in accordance with BS EN ISO 9239-1:2010, Tested in accordance with BS EN ISO 11925- 2:2010

Technical Documents

PIG Grippy Carpeted Entrance and Floor Mat

Storage & Shelf Life of PIG Absorbents & Absorbent Spill Kits

Instructions for PIG Grippy Floor Mat

PIG Grippy Absorbents

Disclaimers

PIG® Grippy® Floor Mat Notice

New Pig adhesive-backed mats are formulated to work with most common industrial and commercial floor surfaces but are not intended for home/residential use and wood flooring. All adhesive mats have some potential to leave residue or lift or discolour finish coatings, paint, and loose or pre-damaged tiles depending on the condition and age of the floor surface. If you have questions about the suitability of New Pig adhesive-backed mats for your application, test a 15 x 15cm piece in a non-critical area before use.

PIG® Grippy® Floor Mats should be replaced if they show signs of wear or damage and should always be changed out every 3 to 6 months, depending on conditions and traffic patterns.

Customer assumes the risk that a New Pig adhesive-backed mat may damage or alter their existing flooring or floor covering. Other than warranties implied by law, New Pig provides no warranty of fitness for a particular purpose and no warranty that an adhesive-backed mat will be fit for customer's intended use. Other than in respect of liability which New Pig cannot lawfully exclude, New Pig shall have no responsibility for, and customer hereby releases and discharges New Pig from, any direct, indirect, incidental or consequential damages to their floors, flooring material, or any other surfaces in their premises. Customer is solely responsible for determining the fitness and appropriateness of the use of New Pig adhesive-backed mats in their premises.



Hogs Hill • Watt Place • Hamilton International Technology Park • Blantyre • Glasgow • G72 0AH 0800 919 900 • newpig.co.uk • pigpen@newpig.com