




PIG® Grippy® Adhesive-Backed Custom-Printed Floor Mat

GRPLM4X6 122cm x 183cm, Absorbs up to 2.36 L

Get Grippy Mat with custom printed logos, promotions and messaging.

- Easy to personalise with your own logo, images or text
- Printed with UL Greenguard Gold Certified ink to meet rigorous chemical emission standards
- Thinner and safer than traditional floor mats; eliminates the need for heavy, outdated rubber-backed floor mats
- Adhesive-backed floor mat stays exactly where you put it with no shifting, bunching up or ripples that cause slips and trips; durable, high-traction surface removes dirt, grime, oil and water from shoes
- Smooth surface delivers higher resolution printing compared to logos on thick, carpeted mats; image won't wrinkle, wear or break apart



Indoors



Heavy Traffic



Dust Control



Absorbing



Antislip



Oil Resistant



NFSI



Carts



Scrub Over



No Bunching



Wheel Chair Friendly



Storage Temperature

Store between 0°C - 49°C

Colour

Black or Grey

Dimensions

122cm W x 183cm L

Mat Weight

Mediumweight

Fluids Absorbed

Water; Grease; Oils

Absorbency

Up to 2.36 L per roll

Perforated

Not Perforated

Temperature Limit

Surface temperatures from 13°C - 49°C

Sold as

1 roll

Weight

1.1 kg

Composition

Absorbent - Polypropylene; Adhesive Backing - Proprietary Adhesive Material

Packaging

Box

Poly-Backing

Poly-Backed

UV Resistant

Yes (Black & Grey only)

Certifications, Approvals and Ratings

NSFI Certified,ANSI B101.1- 2009,DIN 51130:2014 - R13,BS 7976-2:2002+A1:2103 - Low slip,BS EN 13501-1:2007+A1:2009 - Bfl-s1,Tested in accordance with BS EN ISO 9239-1:2010,Tested in accordance with BS EN ISO 11925-2:2010,ASTM G154-1 (Black & Grey only)

Technical Documents

[PIG Grippy Adhesive-Backed Mat](#)

[Storage & Shelf Life of PIG Absorbents & Absorbent Spill Kits](#)

[Technical Data Sheet for PIG® Adhesive Backed Grippy Mat](#)

[Instructions for PIG Grippy Floor Mat](#)

[Grippy Increased Service Life Report](#)

[PIG® Grippy® Adhesive-Backed Floor Mat Scrubber Guidelines](#)

Disclaimers

[PIG® Grippy® Floor Mat Notice](#)

New Pig adhesive-backed mats are formulated to work with most common industrial and commercial floor surfaces but are not intended for home/residential use and wood flooring. All adhesive mats have some potential to leave residue or lift or discolour finish coatings, paint, and loose or pre-damaged tiles depending on the condition and age of the floor surface. If you have questions about the suitability of New Pig adhesive-backed mats for your application, test a 15 x 15cm piece in a non-critical area before use.

PIG® Grippy® Floor Mats should be replaced if they show signs of wear or damage and should always be changed out every 3 to 6 months, depending on conditions and traffic patterns.

Customer assumes the risk that a New Pig adhesive-backed mat may damage or alter their existing flooring or floor covering. Other than warranties implied by law, New Pig provides no warranty of fitness for a particular purpose and no warranty that an adhesive-backed mat will be fit for customer's intended use. Other than in respect of liability which New Pig cannot lawfully exclude, New Pig shall have no responsibility for, and customer hereby releases and discharges New Pig from, any direct, indirect, incidental or consequential damages to their floors, flooring material, or any other surfaces in their premises. Customer is solely responsible for determining the fitness and appropriateness of the use of New Pig adhesive-backed mats in their premises.



Hogs Hill • Watt Place • Hamilton International Technology Park • Blantyre • Glasgow • G72 0AH
0800 919 900 • newpig.co.uk • pigpen@newpig.com