

PIG® Grippy® Adhesive-Backed Floor Mat with Safety Border

GRPSB36200 91cm x 30m, Absorbs up to 30 L

Call attention to hazards and provide a no-slip path for foot traffic with our super-safe, adhesive-backed absorbent runner — its hi-viz yellow border can't be missed!



- Highly visible yellow and black pattern runs down both edges of mat roll, helping you indicate hazards and boost safety
- Durable printed surface withstands industrial wear and tear
- The only floor safety solution that combines a hi-viz border pattern with a high-traction walking surface
- Mat is highly absorbent, very low profile, extremely durable and effortless to maintain
- Adhesive-backed floor mat stays exactly where you put it with no shifting, bunching up or flipping over; traps dirt, salt and moisture to keep it from being tracked around
- Sticks stick to most common commercial floor surfaces, including: concrete, vinyl tile, ceramic tile, quarry tile and linoleum
- Proprietary adhesive sticks to the floor with a super-tight grip, but peels up easily
- Extreme durability that stands up to heavy traffic — even forklifts — stays in place for up to 3 to 6 months, depending on conditions and traffic patterns
- Easy to use: roll out continuous coverage with no gaps, ripples or overlaps that cause slips and trips
- Easy to clean: you can sweep, vacuum, mop, use your shop/wet vac or run your floor scrubber over the mat and it won't budge (cleaning helps to restore hi-viz properties of safety border)
- Easy to customise: lets you create custom-size floor mats that promote the safest path, even around corners
- Highly efficient absorbent top soaks in moisture, wicks and spreads it evenly so the mat dries out quickly
- 91cm x 30m regular mediumweight roll provides enough length to create continuous safety runners around hazards
- Absorbs a wide variety of liquids including water, oil and grease; leakproof backing prevents liquid from soaking through to the floor
- Building Regulations Approved Document M

states that floor surfaces should not impede the movement of wheelchairs (eg. not coir matting) and changes to the floor material should not present a trip hazard; at less than 3mm thick, Grippy Floor Mat is the thinnest commercial floor mat you can buy with no rippled or ramped edges to obstruct doors or create tripping hazards

- Only a fraction of the weight of rubber-backed mats: no more back strain when you change your mats
- Completely eliminates rental mat hassles and can save up to 50% per year over rental contracts
- Has a 91% lower environmental impact than rental floor mats (Please contact us for further details regarding the Life Cycle Assessment report.)
- Classified as slip resistance R13 according to DIN51130 - suitable for use on floors in workrooms and work areas where there is an increased risk of slipping due to grease, oil, water, foods, left-overs, dust, flour, plant clippings, etc.
- Tested in accordance with BS 7976-2:2002+A1:2013, and demonstrated low slip potential in both wet and dry conditions
- Fire classification Bfl-s1 when tested according to BS EN 13501-1
- Tested and Certified by the National Floor Safety Institute (NFSI): when used as part of your floor safety program, high-traction surfaces such as PIG® Safety Border Mat with Adhesive Backing have been proven to reduce slip-and-fall claims by as much as 90%



Item#	Description	Dimensions	Weight
GRPSB36200-BK	Black	91cm W x 30m L	11.36 kg

Item#	Description	Dimensions	Weight
GRPSB36200-BK	Black		

Storage Temperature	Store between 0°C - 49°C
Dimensions	91cm W x 30m L
Mat Weight	Mediumweight
Fluids Absorbed	Water; Grease; Oils
Absorbency	Up to 30 L per roll
Perforated	Not Perforated
Temperature Limit	Surface temperatures from 13°C - 49°C
Sold as	1 roll
Weight	11.36 kg
# per Pallet	38
Composition	Absorbent - Polypropylene; Adhesive Backing - Proprietary Adhesive Material
Packaging	Bag
Poly-Backing	Poly-Backed
UV Resistant	Yes (Black & Grey only)

Certifications, Approvals and Ratings

NSFI Certified,ANSI B101.1- 2009,DIN 51130:2014 - R13,BS 7976-2:2002+A1:2103 - Low slip,BS EN 13501-1:2007+A1:2009 - Bfl-s1,Tested in accordance with BS EN ISO 9239-1:2010,Tested in accordance with BS EN ISO 11925-2:2010,ASTM G154-1 (Black & Grey only)

Technical Documents

[PIG Grippy Adhesive-Backed Mat](#)

[Storage & Shelf Life of PIG Absorbents & Absorbent Spill Kits](#)

[Technical Data Sheet for PIG® Adhesive Backed Grippy Mat](#)

[Instructions for PIG Grippy Floor Mat](#)

[Grippy Increased Service Life Report](#)

[PIG® Grippy® Adhesive-Backed Floor Mat Scrubber Guidelines](#)

Disclaimers

[PIG® Grippy® Floor Mat Notice](#)

New Pig adhesive-backed mats are formulated to work with most common industrial and commercial floor surfaces but are not intended for home/residential use and wood flooring. All adhesive mats have some potential to leave residue or lift or discolour finish coatings, paint, and loose or pre-damaged tiles depending on the condition and age of the floor surface. If you have questions about the suitability of New Pig adhesive-backed mats for your application, test a 15 x 15cm piece in a non-critical area before use.

PIG® Grippy® Floor Mats should be replaced if they show signs of wear or damage and should always be changed out every 3 to 6 months, depending on conditions and traffic patterns.

Customer assumes the risk that a New Pig adhesive-backed mat may damage or alter their existing flooring or floor covering. Other than warranties implied by law, New Pig provides no warranty of fitness for a particular purpose and no warranty that an adhesive-backed mat will be fit for customer's intended use. Other than in respect of liability which New Pig cannot lawfully

exclude, New Pig shall have no responsibility for, and customer hereby releases and discharges New Pig from, any direct, indirect, incidental or consequential damages to their floors, flooring material, or any other surfaces in their premises. Customer is solely responsible for determining the fitness and appropriateness of the use of New Pig adhesive-backed mats in their premises.



World's best stuff for leaks, drips and spills.

Hogs Hill • Watt Place • Hamilton International Technology Park • Blantyre • Glasgow • G72 0AH

0800 919 900 • newpig.co.uk • pigpen@newpig.com