

PIG® Grippy® Adhesive-Backed Floor Mat

GRP72203 183cm x 6m, Absorbs up to 13.2 L

Hassling with rubber-backed floor mats or rental mats? Prevent slips, trips and falls in high-traffic areas with our easy-to-clean, adhesive-backed commercial floor mat. Perfect for grocery and retail environments.

– Now there’s a whole new way to keep your floor safe — PIG Grippy Floor Mat is highly absorbent, very low profile, extremely durable and effortless to maintain
– Adhesive-backed floor mat stays exactly where you put it with no shifting, bunching up or flipping over; traps dirt, salt and moisture to keep it from being tracked around
– PIG Grippy Floor Mat will stick to most common commercial floor surfaces, including: concrete, vinyl tile, ceramic tile, quarry tile and linoleum
– Proprietary adhesive sticks to the floor with a super-tight grip, but peels up easily
– Extreme durability that stands up to heavy traffic — even forklifts — stays in place for up to 3 to 6 months, depending on conditions and traffic patterns
– Easy to use: roll out continuous walk-off coverage for entrances and walkways with no gaps, ripples or overlaps that cause slips and trips
– Easy to clean: you can sweep, vacuum, mop, use your shop/wet vac or run your floor scrubber over Grippy Mat and it won’t budge
– Easy to customise: lets you create custom-size floor mats for transition areas and wet problem spots
– Highly efficient absorbent top soaks in moisture, wicks and spreads it evenly so the mat dries out quickly — ideal for entrances and anywhere you need maximum absorbency for water
– Roll of two precut 183cm x 3m mediumweight mats provides enough coverage to create continuous walk-off runners to stop dirt and moisture at the door
– Available in a choice of colours to match your surroundings
– Absorbs a wide variety of liquids including water, oil and grease; leakproof backing prevents liquid from soaking through to the floor
– The thinnest commercial floor mat you can buy: no rippled edges to obstruct doors or

create tripping hazards. ADA compliant for wheelchairs and prams; carts and pallet trucks roll right over it
– Only a fraction of the weight of rubber-backed mats: no more back strain when you change your mats
– Completely eliminates rental mat hassles and can save up to 50% per year over rental contracts
– PIG Grippy Floor Mat has a 91% lower environmental impact than rental floor mats (Please contact us for further details regarding the Life Cycle Assessment report.)
– PIG Grippy Floor Mat classified as slip resistance R12 according to EN 16165:2021 Annex B - suitable for use on floors in workrooms and work areas where there is an increased risk of slipping due to grease, oil, water, foods, left-overs, dust, flour, plant clippings, etc.
– PIG Grippy Floor Mat demonstrated a low slip potential under both wet and dry test conditions when tested to EN 16165:2021 Annex C
– Fire classification Bfl-s1 when tested according to BS EN 13501-1
– Tested and Certified by the National Floor Safety Institute (NFSI): when used as part of your floor safety program, high-traction surfaces such as PIG Grippy Floor Mat have been proven to reduce slip-and-fall claims by as much as 90%
– VIDEO:
– Click here to watch PIG Grippy Floor Mat flat out beats rental mats Video



Item#	Description	Dimensions	Weight
GRP72203-GY	Grey	183cm W x 6m L	4.8 kg
GRP72203-BK	Black	183cm W x 6m L	4.8 kg

Item#	Description	Dimensions	Weight

GRP72203-GY	Grey
GRP72203-BK	Black

Storage Temperature	Store between 0°C - 49°C
Dimensions	183cm W x 6m L
Mat Weight	Mediumweight
Fluids Absorbed	Oils, Coolants, Solvents & Water
Absorbency	Up to 13.2 L per roll
Perforated	Not Perforated
Temperature Limit	Surface temperatures from 13°C - 49°C
Sold as	1 roll
Weight	4.8 kg
# per Pallet	56
Composition	Absorbent - Polypropylene; Adhesive Backing - Proprietary Adhesive Material
Packaging	Bag
Poly-Backing	Poly-Backed
UV Resistant	Yes (Black & Grey only)

Certifications, Approvals and Ratings

NSFI Certified,ANSI B101.1- 2009,Tested in accordance with BS EN ISO 9239-1:2010,Tested in accordance with BS EN ISO 11925-2:2010,ASTM G154-1 (Black & Grey only),BS EN 13501-1:2018 - Bfl-s1,EN 16165:2021 Annex B - R12,EN 16165:2021 Annex C - Low slip

Technical Documents

PIG Grippy Adhesive-Backed Mat

Instructions for PIG Grippy Floor Mat

Technical Data Sheet for PIG® Adhesive Backed Grippy Mat

Storage & Shelf Life of PIG Absorbents & Absorbent Spill Kits

Grippy Increased Service Life Report

PIG® Grippy® Adhesive-Backed Floor Mat Scrubber Guidelines

Disclaimers

PIG® Grippy® Floor Mat Notice

New Pig adhesive-backed mats are formulated to work with most common industrial and commercial floor surfaces but are not intended for home/residential use and wood flooring. All adhesive mats have some potential to leave residue or lift or discolour finish coatings, paint, and loose or pre-damaged tiles depending on the condition and age of the floor surface. If you have questions about the suitability of New Pig adhesive-backed mats for your application, test a 15 x 15cm piece in a non-critical area before use.

PIG® Grippy® Floor Mats should be replaced if they show signs of wear or damage and should always be changed out every 3 to 6 months, depending on conditions and traffic patterns.

Customer assumes the risk that a New Pig adhesive-backed mat may damage or alter their existing flooring or floor covering. Other than warranties implied by law, New Pig provides no warranty of fitness for a particular purpose and no warranty that an adhesive-backed mat will be fit for customer's intended use. Other than in respect of liability which New Pig cannot lawfully exclude, New Pig shall have no responsibility for, and customer hereby releases and discharges New Pig from, any direct, indirect, incidental or consequential damages to their floors, flooring material, or any other surfaces in their premises. Customer is solely responsible for determining the fitness and appropriateness of the use of New Pig adhesive-backed mats in their premises.

New Pig
World's best stuff for leaks, drips and spills.

Hogs Hill • Watt Place • Hamilton International Technology Park • Blantyre • Glasgow • G72 0AH
0800 919 900 • newpig.co.uk • pigpen@newpig.com