

PIG® Grippy® Social Distancing Floor Sign – Box of 4

GMM21004 61cm W x 43cm L, 4 Pads per Box

Perfect liquid-trapping non-slip floor sign to help reduce falls, slips, and trip hazards while clearly marking out and managing COVID-19 social distancing and queuing systems in your premises.

- A long-lasting solution that stays in place for up to 12 weeks!
- Highly visible contrast print will not wear off and stands out to help communicate important safety messages.
- Easy to apply, reposition and remove. Sticks to most commercial floor surfaces including concrete, vinyl, ceramic and quarry tiles, and linoleum flooring. Non-permanent adhesive backing pulls up easily and will not leave residue or damage floors.
- Easy to clean. No need to remove when sanitising floors. Mat and markings can withstand regular mop or floor scrubber cleaning; can be scrubbed, vacuumed, or swept off frequently without affecting appearance or performance.
- Extremely durable adhesive-backed mat that is made to withstand heavy foot, cart and other wheeled traffic.
- Low profile mat reduces tripping hazard and carts, wheelchairs, prams, and walkers glide right over it.
- Recommended for indoor use only.



Item#	Description	Dimensions	Weight
GMM21004-BK	Black	61cm W x 43cm L	0.87 kg

Metric Equivalent:

Item#	Description	Dimensions	Weight
GMM21004-BK	Black		

Specifications

Dimensions	61cm W x 43cm L
Mat Weight	Mediumweight
Fluids Absorbed	Oils, Coolants, Solvents & Water

Absorbency	N/A
Perforated	Not Perforated
Storage Temp Range	Store between 0°C - 49°C
Temperature Limit	Surface temperatures from 13°C to 49°C
Sold as	4 pads per box
Weight	0.87 kg
New Pig Patent	Pending
# per Pallet	100
Composition	Absorbent - Polypropylene; Adhesive Backing - Proprietary Adhesive Material
Packaging	Box
Poly-Backing	Poly-Backed
UV Resistant	Yes

Technical Information

Certifications, Approvals and Ratings

NSFI Certified,ANSI B101.1- 2009,DIN 51130:2014 - R13,BS 7976-2:2002+A1:2103 - Low slip,BS EN 13501-1:2007+A1:2009 - Bfl-s1,Tested in accordance with BS EN ISO 9239-1:2010,Tested in accordance with BS EN ISO 11925-2:2010,ASTM G154-1 (Black & Grey only)

Technical Documents

[PIG Adhesive-Backed Mat](#)

[Storage & Shelf Life of PIG Absorbents & Absorbent Spill Kits](#)

[Instructions for PIG Grippy Floor Mat](#)

[PIG Grippy Absorbents](#)

Disclaimers

PIG® Grippy® Floor Mat Notice

New Pig adhesive-backed mats are formulated to work with most common industrial and commercial floor surfaces but are not intended for home/residential use and wood flooring. All adhesive mats have some potential to leave residue or lift or discolour finish coatings, paint, and loose or pre-damaged tiles depending on the condition and age of the floor surface. If you have questions about the suitability of New Pig adhesive-backed mats for your application, test a 15 x 15cm piece in a non-critical area before use.

PIG® Grippy® Floor Mats should be replaced if they show signs of wear or damage and should always be changed out every 3 to 6 months, depending on conditions and traffic patterns.

Customer assumes the risk that a New Pig adhesive-backed mat may damage or alter their existing flooring or floor covering. Other than warranties implied by law, New Pig provides no warranty of fitness for a particular purpose and no warranty that an adhesive-backed mat will be fit for customer's intended use. Other than in respect of liability which New Pig cannot lawfully exclude, New Pig shall have no responsibility for, and customer hereby releases and discharges New Pig from, any direct, indirect, incidental or consequential damages to their floors, flooring material, or any other surfaces in their premises. Customer is solely responsible for determining the fitness and appropriateness of the use of New Pig adhesive-backed mats in their premises.