

# PIG® High Flow Leak Diverter

TLS676 340cm x 340cm

High flow design catches and diverts up to 38-litres per minute to prevent large leaks from becoming a big problem.

- Hangs easily in problem spots to catch high volume leaks and channel them to a floor drain or collection container
- Nonpermeable tarp is vinyl coated for strength and durability; resists punctures, UV and mildew for long life
- 76mm diameter flat hose drains up to 38-litres of liquid per minute without backing up
- Pinched corners help funnel liquid toward centre for better drainage
- Grommets resist tearing and make installation easy
- Cut drain hose for a custom fit; insert 90-degree elbow between hose sections to prevent kinking (hose and clamps included)
- Ideal for washdowns; prevents wet floors and makes for easier clean up



Item#	Description	Dimensions	Weight
TLS676-TR	Translucent	340cm W x 340cm L	7.6 kg

## Metric Equivalent:

Item#	Description	Dimensions	Weight
TLS676-TR	Translucent		

## Specifications

Use With	Roofs
Drainage Hose	Included
Hanging Straps	Sold separately
Corner Style	D-Ring Corner
Additional Grommets per Side	3 per side, 91cm spacing
Total Grommets/D-Rings	12 Grommets and 4 D-Rings
Installation Method	Hanging Straps
Style	Square
Dimensions	340cm W x 340cm L

<b>Sold as</b>	1 each
<b>Weight</b>	7.6 kg
<b>Composition</b>	13oz PVC/Polyester, with Vinyl Hose & PVC Elbow
<b>Flow Rate</b>	38 ltr. per minute
<b>Includes</b>	1 - 340cm x 340cm Leak Diverter 1 - 762cm L x 7.6cm Dia Flat Hose 1 - 90-degree Elbow 2 - Hose Clamps

## Technical Documents

[Instructions for PIG High Flow Roof Leak Diverter](#)

## Disclaimers

[Maximum Working Temperature](#)

Not suitable for temperatures over 170°F/77°C.

[Nominal Dimensions](#)

Dimensions are nominal size due to pinched corners and reinforced side walls.



Hogs Hill • Watt Place • Hamilton International Technology Park • Blantyre • Glasgow • G72 0AH  
 0800 919 900 • [newpig.co.uk](http://newpig.co.uk) • [pigpen@newpig.com](mailto:pigpen@newpig.com)