

PIG® High-Reach Leak Diverter

TLS564 30cm x 28cm

Telescoping pole extends into place to install a Leak Diverter up to 6m in the air without a ladder.

- Lengthen telescoping pole to quickly catch leaks and channel them to a floor drain or collection container
- Tension mounted pole with rubber cups secures pole to floor and ceiling
- Makes it easy for one person to install or move a Leak Diverter from one location to another
- Nonpermeable tarp is vinyl-coated for strength and durability; resists punctures, UV and mildew for long life
- Hose sold separately



Item#	Description	Dimensions	Weight
TLS564-YW	Yellow	ext. dia. 30cm x 28cm H	2.3 kg

Item#	Description	Dimensions	Weight
TLS564-YW	Yellow		

Use With	Pipes & Roofs
Drainage Hose	Sold separately
Hanging Straps	N/A
Corner Style	N/A
Additional Grommets per Side	N/A
Total Grommets/D-Rings	N/A
Installation Method	Telescoping Pole
Style	Cone
Dimensions	ext. dia. 30cm x 28cm H

Hose Connector	.75"
Sold as	1 each
Weight	2.3 kg
# per Pallet	42
Composition	Diverter - 18oz PVC/Polyester; Spring-Loaded Pole - Aluminum; Wire Frame - Steel; Pole End Fittings - Rubber
Flow Rate	12.6 ltr. per Minute

Technical Documents

[PIG High-Reach Leak Diverter Installation Guide](#)

Disclaimers

[Maximum Working Temperature](#)

Not suitable for temperatures over 170°F/77°C.



Hogs Hill • Watt Place • Hamilton International Technology Park • Blantyre • Glasgow • G72 0AH
0800 919 900 • newpig.co.uk • pigpen@newpig.com