

PIG® High-Volume SpillBlocker® Dike

PLR253 10cm x 152cm x 11cm, 100% Polyurethane, 1 each

Our tallest SpillBlocker dikes are designed to handle high-volume spills and pooling liquids.

- Exclusive New Pig formulation features a tear-resistant top layer and a flexible, tacky bottom layer that seals tight to smooth surfaces and blocks liquids
- Taller height is great for containing deeper pools of liquid and larger flows
- Built-in dovetail connectors create a liquid-proof seal and allow you to join as many sections as you need without extra parts
- Fast protection for when a large spill is heading right for your drain
- Confines and diverts fluids without absorbing them, making cleanup or reclamation simpler
- High-visibility lime-green top colour draws attention to spill for increased safety
- Polyurethane material resists water, oils and many chemicals
- Smaller sections are easy to handle and deploy
- Reusable dike cleans easily with soap and water



Item#	Description	Dimensions	Weight
PLR253-NG	Neon Green	10cm W x 152cm L x 11cm H	7.26 kg

Item#	Description	Dimensions	Weight
PLR253-NG	Neon Green		

Style	Non-Weight Bearing
Dimensions	10cm W x 152cm L x 11cm H
Intended For	Use on Smooth Surface
Max liquid temp exposure	Max Exposure Limit 107°C (225°F) for up to 30 Minutes
Storage Temp Range	Store from -18°C (0°F) to 49°C (120°F)
Temperature Limit	Works from -18°C (0°F) to 71°C (160°F) up to 12 months

Sold as	1 per box
Weight	7.26 kg
New Pig Patent	5,236,281
# per Pallet	20
Composition	100% Polyurethane

Technical Documents

[PIG SpillBlocker Dikes, DrainBlocker Drain Covers and other Blockers](#)

[Urethane Use, Care and Storage](#)

[Technical Data Sheet for PIG® Blocker Products](#)

[Environmental Protection Act 1990](#)

[Water Resources Act 1991](#)

Disclaimers

[Urethane Notice](#)

Due to the nature of softer urethane, the physical properties of these products may change over time with exposure to certain environmental conditions like temperature, humidity and UV radiation. Typical life expectancy is 5 years. Please inspect the stored product regularly to ensure it is in a usable state. For optimum performance, ensure that the area where the product will be deployed is free of debris, cracks and holes. For more details and for chemical compatibility, please call Technical Services.



Hogs Hill • Watt Place • Hamilton International Technology Park • Blantyre • Glasgow • G72 0AH
0800 919 900 • newpig.co.uk • pigpen@newpig.com