



PIG® HoofTrax™ Adhesive-Backed Runner - Sand Texture

FLM6200 1 roll, Sand

Add traction in areas where absorbency isn't needed or permitted. Runner with Sand Texture is crystal clear for easy inspections.

- HoofTrax Runners are the perfect non-absorbent solution for areas that just need traction
- Crystal clear properties help you meet cleaning standards, making it easy to inspect for dirt and grime
- Practically invisible once installed, better than most other "clear" treads that appear frosted or translucent
- Sand Texture surface is gritty, but non-abrasive, to help create safer footing around air blades, passageways, freezers and chiller cabinets
- Provides a walking surface that's tested and certified, wet or dry, to be "low slip risk"; offers remediation for floors that are otherwise potential slip hazards
- Ideal solution for paths of main foot traffic; covers unsightly wear patterns as well as wear-polished slick spots
- Simple peel-and-stick application adheres to ceramic tile, porcelain tile, VCT, sealed concrete and more
- Vinyl construction with polyester film is easy to clean with mops and floor scrubbers; won't interfere with normal workplace cleaning services
- Stays in place up to 3 to 12 months, depending on conditions



Heavy Traffic



Antislip



Carts



Indoors



Wheel Chair Friendly



Scrub Over



Item#	Description	Dimensions	Weight
FLM6200-1103	27" x 50'	FLM6200-1102 - 69cm W x 1.5m L FLM6200-1103 - 69cm W x 15.2m L	FLM6200-1102 - .91 kg FLM6200-1103 - 4.2 kg

FLM6200-1102	27" x 5'	FLM6200-1102 - 69cm W x 1.5m L	FLM6200-1102 - .91 kg
		FLM6200-1103 - 69cm W x 15.2m L	FLM6200-1103 - 4.2 kg

Item#	Description	Dimensions	Weight
FLM6200-1103	27" x 50'		
FLM6200-1102	27" x 5'		

Intended Use	Indoor Use on Ceramic Tile, Porcelain Tile, VCT & Concrete
Antimicrobial	No
Indoor/Outdoor	Indoor Use
Traffic	Heavy Foot Traffic
Colour	Clear
Dimensions	FLM6200-1102 - 69cm W x 1.5m L
Dimensions	FLM6200-1103 - 69cm W x 15.2m L
Temperature Limit	Application: > -25°F (-32°C); Operating: -35°F (-37°C) to 400°F (204°C)
Texture	Sand
Sold as	1 roll
Weight	FLM6200-1102 - .91 kg
Weight	FLM6200-1103 - 4.2 kg
# per Pallet	FLM6200-1102 - 220
# per Pallet	FLM6200-1103 - 117
Composition	Film: Polyester; Adhesive Backing: Proprietary Adhesive Material
Thickness	0.5mm

Certifications, Approvals and Ratings
BS EN 13501-1:2018 - Bfl-s1,EN 16165:2021 Annex C - Low slip,EN 16165:2021 Annex B - R11

Technical Documents

[Instructions for HoofTrax Adhesive-Backed Runner](#)

Disclaimers

Adhesive Notice

All adhesive mats have some potential to leave residue, lift and/or discolour 1) surface finish, 2) surface coating, 3) paint, 4) loose or previously damaged tiles. For these reasons and others, if you have questions about the suitability of New Pig Adhesive-Backed Mats or Films for your application, test a small section of the mat in a discreet or non-critical area before using on larger areas.

Suitable Surface Notice - Sand Texture

New Pig Adhesive-Backed Mats and Films are formulated to work with most common hard-floor surfaces. DO NOT use this product on wood flooring with stains, finishes or coatings.

