# PIG® Leak Diverter for Pipes - Horizontal

TLS147 72cm x 41cm



Purpose-built design catches pipe leaks or condensation to protect equipment, inventory and personnel.

- Material wraps completely around 1.9cm to 10cm diameter pipes to capture and contain sprays, drips and accumulated condensation
- Nonpermeable tarp is vinyl-coated for strength and durability; resists punctures, UV and mildew for long life
- Tapered design helps funnel liquid toward centre for better drainage
- Hook-and-loop fasteners make installation quick and easy and secures diverter in place
- Accepts a standard 3/4" hose connection to channel liquid to floor drain or collection container (hose sold separately)
- Flow rate of 12.6-litres per minute when used with a 1/2" ID hose





| Item# | Description | Dimensions | Weight |
|---|---|---|---|
| TLS147-YW | Yellow | 72cm W x 41cm H | .3 kg |

| Item# | Description | Dimensions | Weight |
|---|---|---|---|
| TLS147-YW | Yellow | | |

| | |
|---|---|
| **Use With** | 1.9cm to 10cm Pipes |
| **Drainage Hose** | Sold separately |
| **Hanging Straps** | N/A |
| **Corner Style** | N/A |
| **Additional Grommets per Side** | N/A |
| **Total Grommets/D-Rings** | N/A |
| **Installation Method** | Velcro |
| **Style** | Wraparound |
| **Dimensions** | 72cm W x 41cm H |
| **Hose Connector** | .75" |
| **Sold as** | 1 per bag |

| | |
|---|---|
| **Weight** | .3 kg |
| **Composition** | 18oz PVC/Polyester |
| **Flow Rate** | 12.6 ltr. per Minute |

## Technical Documents

REACH Statement

PIG Leak Diverter for Spraying Pipes Installation Guide

## Disclaimers

Maximum Working Temperature

Not suitable for temperatures over 170°F/77°C.

New Pig
World's best stuff for leaks, drips and spills.

Hogs Hill • Watt Place • Hamilton International Technology Park • Blantyre • Glasgow • G72 0AH
0800 919 900 • newpig.co.uk • pigpen@newpig.com