


## PIG® Leak Diverter for Pipes

TLS200 30.5cm x 30.5cm

Purpose-built design catches pipe leaks or condensation to protect equipment, inventory and personnel.

- Hangs from a leaking pipe to catch nuisance leaks and channel them to a floor drain or collection container
- Nonpermeable tarp is vinyl-coated for strength and durability; resists punctures, UV and mildew for long life
- Built-in grommets and included rubber straps make it easy to hang from an overhead pipe
- Choose yellow for high visibility, grey to blend with plant ceilings or clear to monitor leaks
- Flow rate of 12.6-litres per minute when used with a 1/2" ID hose



Item#	Description	Dimensions	Weight
TLS200-YW	Yellow	ext. dia. 30.5cm x 30.5cm H	0.9 kg
TLS200-GY	Grey	ext. dia. 30.5cm x 30.5cm H	0.9 kg
TLS200-CL	Clear	ext. dia. 30.5cm x 30.5cm H	0.9 kg

### Metric Equivalent:

Item#	Description	Dimensions	Weight
TLS200-YW	Yellow		
TLS200-GY	Grey		
TLS200-CL	Clear		

### Specifications

<b>Use With</b>	Pipes
<b>Dimensions</b>	ext. dia. 30.5cm x 30.5cm H
<b>Drainage Hose Included</b>	No
<b>Grommets/D-Rings</b>	4 Grommets
<b>Hanging Straps Included</b>	Four 36cm L

<b>Hose Connector</b>	.75"
<b>Installation Method</b>	Hanging Straps
<b>Sold as</b>	1 each
<b>Weight</b>	0.9 kg
<b># per Pallet</b>	504
<b>Composition</b>	Diverter (Colours) - PVC, Polyester; Diverter (Clear) - PVC w/ Polyester Reinforcement; Straps - Rubber
<b>Flow Rate</b>	12.6 ltr. per Minute
<b>Includes</b>	1 - Leak Diverter 1 - 3/4" Drain Fitting 4 - 36cm L Rubber Straps (TLS470)
<b>Thickness</b>	Clear - 300 micron, Colours - 400 micron

## Disclaimers

### Maximum Working Temperature

Not suitable for temperatures over 170°F/77°C.



Hogs Hill • Watt Place • Hamilton International Technology Park • Blantyre • Glasgow • G72 0AH  
0800 919 900 • [newpig.co.uk](http://newpig.co.uk) • [pigpen@newpig.com](mailto:pigpen@newpig.com)