









PIG® Leak Diverter for Roofs

TLS463 213cm x 213cm

Stop devastating roof leak damage and protect your people, equipment and inventory with the original diverter. Invented here!

- The original Leak Diverter invented here and engineered to stop devastating roof leak damage every time, guaranteed
- Hangs easily in problem spots to catch nuisance leaks and channel them to a floor drain or collection container
- Ideal for quick response to avoid downtime after a roof leak or for long-term prevention in leakprone areas
- Nonpermeable tarp is vinyl coated for strength and durability; resists punctures, UV and mildew for long life
- Pinched corners help funnel liquid toward centre for better drainage
- Accepts a standard 3/4" hose connection to channel liquid to floor drain or collection container (hose sold separately)
- Flow rate of 12.6-litres per minute when used with a 1/2" ID hose
- Grommets resist tearing and make installation easy



| Item# | Description | Dimensions | Weight |
|-----------|-------------|-------------------|---------|
| TLS463-TR | Translucent | 213cm W x 213cm L | 2.72 kg |
| TLS463-GY | Grey | 213cm W x 213cm L | 2.72 kg |
| TLS463-CL | Clear | 213cm W x 213cm L | 2.72 kg |

Metric Equivalent:

| Item# | Description | Dimensions | Weight | |
|-----------|-------------|------------|--------|--|
| TLS463-TR | Translucent | | | |
| TLS463-GY | Grey | | | |
| TLS463-CL | Clear | | | |

Specifications

| Use With | Roofs |
|---------------|-----------------|
| Drainage Hose | Sold separately |

| Hanging Straps | Sold separately |
|------------------------------|-----------------------------------|
| Corner Style | 7.5cm Pinched Corner with Grommet |
| Additional Grommets per Side | 1 per side, 107cm spacing |
| Total Grommets/D-Rings | 8 Grommets |
| Installation Method | Hanging Straps |
| Style | Square |
| Dimensions | 213cm W x 213cm L |
| Hose Connector | .75" |
| Sold as | 1 each |
| Weight | 2.72 kg |
| Composition | 13oz PVC/Polyester |
| Flow Rate | 12.6 ltr. per Minute |

Technical Documents

REACH Statement

Instructions for PIG Leak Diverter Systems

Disclaimers

Maximum Working Temperature

Not suitable for temperatures over 170°F/77°C.

Nominal Dimensions

Dimensions are nominal size due to pinched corners and reinforced side walls.



Hogs Hill • Watt Place • Hamilton International Technology Park • Blantyre • Glasgow • G72 0AH 0800 919 900 • newpig.co.uk • pigpen@newpig.com