

# PIG® Leak Diverter for Roofs

TLS466 457cm x 457cm

Stop devastating roof leak damage and protect your people, equipment and inventory with the original diverter. Invented here!



- The original Leak Diverter - invented here and engineered to stop devastating roof leak damage every time, guaranteed
- Hangs easily in problem spots to catch nuisance leaks and channel them to a floor drain or collection container
- Ideal for quick response to avoid downtime after a roof leak or for long-term prevention in leak-prone areas
- Nonpermeable tarp is vinyl coated for strength and durability; resists punctures, UV and mildew for long life
- Pinched corners help funnel liquid toward centre for better drainage
- Accepts a standard 3/4" hose connection to channel liquid to floor drain or collection container (hose sold separately)
- Flow rate of 12.6-litres per minute when used with a 1/2" ID hose
- Heavy D-rings and grommets resist tearing and make installation easy



| Item#     | Description | Dimensions        | Weight  |
|-----------|-------------|-------------------|---------|
| TLS466-TR | Translucent | 457cm W x 457cm L | 9.98 kg |
| TLS466-GY | Grey        | 457cm W x 457cm L | 9.98 kg |
| TLS466-CL | Clear       | 457cm W x 457cm L | 9.98 kg |

| Item#     | Description | Dimensions | Weight |
|-----------|-------------|------------|--------|
| TLS466-TR | Translucent |            |        |
| TLS466-GY | Grey        |            |        |
| TLS466-CL | Clear       |            |        |

|                      |                 |
|----------------------|-----------------|
| <b>Use With</b>      | Roofs           |
| <b>Drainage Hose</b> | Sold separately |

|                                     |  |
|-------------------------------------|--|
| <b>Hanging Straps</b>               | Sold separately                          |
| <b>Corner Style</b>                 | D-Ring Corner                            |
| <b>Additional Grommets per Side</b> | 3 per side, 114cm spacing                |
| <b>Total Grommets/D-Rings</b>       | 16 Grommets and 4 D-Rings                |
| <b>Installation Method</b>          | Hanging Straps                           |
| <b>Style</b>                        | Square                                   |
| <b>Dimensions</b>                   | 457cm W x 457cm L                        |
| <b>Hose Connector</b>               | .75"                                     |
| <b>Sold as</b>                      | 1 each                                   |
| <b>Weight</b>                       | 9.98 kg                                  |
| <b>Composition</b>                  | 13oz PVC/Polyester                       |
| <b>Flow Rate</b>                    | 12.6 ltr. per Minute                     |
| <b>Thickness</b>                    | Clear - 300 micron, Colours - 400 micron |

## Technical Documents

[REACH Statement](#)

[Instructions for PIG Leak Diverter Systems](#)

## Disclaimers

[Maximum Working Temperature](#)

Not suitable for temperatures over 170°F/77°C.

[Nominal Dimensions](#)

Dimensions are nominal size due to pinched corners and reinforced side walls.



Hogs Hill • Watt Place • Hamilton International Technology Park • Blantyre • Glasgow • G72 0AH  
0800 919 900 • [newpig.co.uk](http://newpig.co.uk) • [pigpen@newpig.com](mailto:pigpen@newpig.com)