# PIG® Leak Diverter for Roofs

TLS561 41cm x 457cm

Stop devastating roof leak damage and protect your people, equipment and inventory with the original diverter. Invented here!

- The original Leak Diverter - invented here and engineered to stop devastating roof leak damage every time, guaranteed
- Long, rectangular shape is ideal for catching leaks or accumulated condensation along cracks, fissures or pipes
- Hangs easily in problem spots to catch nuisance leaks and channel them to a floor drain or collection container
- Ideal for quick response to avoid downtime after a roof leak or for long-term prevention in leak-prone areas
- Nonpermeable tarp is vinyl coated for strength and durability; resists punctures, UV and mildew for long life
- Pinched corners help funnel liquid toward centre for better drainage
- Grommets resist tearing and make installation easy
- 41cm width fits easily between joists
- Accepts a standard 3/4" hose connection to channel liquid to floor drain or collection container (hose sold separately)
- Flow rate of 12.6-litres per minute when used with a 1/2" ID hose
- Edges feature rods along length for additional stability
- Rods split at 152cm lengths for easy storage

| Item# | Description | Dimensions | Weight |
|---|---|---|---|
| TLS561-TR | Translucent | 41cm W x 457cm L | 4.1 kg |


| Item# | Description | Dimensions | Weight |
|---|---|---|---|
| TLS561-TR | Translucent | | |

| | |
|---|---|
| **Use With** | Roofs |
| **Drainage Hose** | Sold separately |
| **Hanging Straps** | Sold separately |
| **Corner Style** | 7.5cm Pinched Corner with Grommet |
| **Additional Grommets per Side** | 3 per long side, 114cm spacing |
| **Total Grommets/D-Rings** | 10 Grommets |
| **Installation Method** | Hanging Straps |
| **Style** | Trough Style |
| **Dimensions** | 41cm W x 457cm L |
| **Hose Connector** | .75" |
| **Sold as** | 1 each |
| **Weight** | 4.1 kg |
| **# per Pallet** | 96 |
| **Composition** | 13oz PVC/Polyester |
| **Flow Rate** | 12.6 ltr. per Minute |

## Technical Documents

REACH Statement

Instructions for PIG Trough Style Roof Leak Diverter

## Disclaimers

### Maximum Working Temperature

Not suitable for temperatures over 170°F/77°C.

### Nominal Dimensions

Dimensions are nominal size due to pinched corners and reinforced side walls.

New Pig
World's best stuff for leaks, drips and spills.

Hogs Hill • Watt Place • Hamilton International Technology Park • Blantyre • Glasgow • G72 0AH
0800 919 900 • newpig.co.uk • pigpen@newpig.com