

PIG® Low-Profile Leak Diverter

TLS190 29cm x 23cm

Leaky pipe in a tight spot? Low-profile design is great for capturing leaks where full-size designs can't fit.

- Low-profile design and compact size let you target a specific leak in tight spaces
- Nonpermeable material is vinyl-coated for strength and durability; resists punctures and mildew for long life
- UV resistant up to 12 months for long-term outdoor use without degradation
- Built-in grommets and rubber straps (sold separately) make it easy to hang from an overhead pipe
- Accepts a standard 3/4" hose connection to safely channel liquid to floor drain or collection container (hose sold separately)
- Flow rate of 12.6-litres per minute when used with a 1/2" ID hose



Specifications

Use With	Pipes & Roofs
Drainage Hose	Sold separately
Hanging Straps	Sold separately
Corner Style	N/A
Additional Grommets per Side	N/A
Total Grommets/D-Rings	4 Grommets
Installation Method	Hanging Straps
Style	Cone
Colour	Yellow
Dimensions	ext. dia. 29cm x 23cm H
Hose Connector	.75"
Sold as	1 each
Weight	.5 kg
Composition	18oz PVC/Polyester

Flow Rate	12.6 ltr. per Minute
Includes	1 - Leak Diverter 1 - 3/4" Drain Fitting 6 - Grommets

Technical Documents

[Instructions for PIG Leak Diverter Systems](#)

Disclaimers

[Maximum Working Temperature](#)

Not suitable for temperatures over 170°F/77°C.



New Pig

World's best stuff for leaks, drips and spills.

Hogs Hill • Watt Place • Hamilton International Technology Park • Blantyre • Glasgow • G72 0AH
0800 919 900 • newpig.co.uk • pigpen@newpig.com