

## PIG® Low-Profile Leak Diverter

TLS190 29cm x 23cm

Leaky pipe in a tight spot? Low-profile design is great for capturing leaks where full-size designs can't fit.

- Low-profile design and compact size let you target a specific leak in tight spaces
- Nonpermeable material is vinyl-coated for strength and durability; resists punctures and mildew for long life
- UV resistant up to 12 months for long-term outdoor use without degradation
- Built-in grommets and rubber straps (sold separately) make it easy to hang from an overhead pipe
- Accepts a standard 3/4" hose connection to safely channel liquid to floor drain or collection container (hose sold separately)
- Flow rate of 12.6-litres per minute when used with a 1/2" ID hose



<b>Use With</b>	Pipes & Roofs
<b>Drainage Hose</b>	Sold separately
<b>Hanging Straps</b>	Sold separately
<b>Corner Style</b>	N/A
<b>Additional Grommets per Side</b>	N/A
<b>Total Grommets/D-Rings</b>	4 Grommets
<b>Installation Method</b>	Hanging Straps
<b>Style</b>	Cone
<b>Colour</b>	Yellow
<b>Dimensions</b>	ext. dia. 29cm x 23cm H
<b>Hose Connector</b>	.75"
<b>Sold as</b>	1 each
<b>Weight</b>	.5 kg
<b>Composition</b>	18oz PVC/Polyester

**Flow Rate**

12.6 ltr. per Minute

**Includes**

1 - Leak Diverter  
1 - 3/4" Drain Fitting  
6 - Grommets

**Technical Documents**

[Instructions for PIG Leak Diverter Systems](#)

**Disclaimers**

[Maximum Working Temperature](#)

Not suitable for temperatures over 170°F/77°C.



Hogs Hill • Watt Place • Hamilton International Technology Park • Blantyre • Glasgow • G72 0AH  
0800 919 900 • [newpig.co.uk](http://newpig.co.uk) • [pigpen@newpig.com](mailto:pigpen@newpig.com)