





PIG® Oil-Only Absorbent Booms

BOM408 13cm x 6m, Absorbs up to 90.8 L per bag, 2 booms

Control oil spills on land or water with the fieldproven performance of PIG Booms.

- Field-proven performance works in all conditions to absorb oil spills on land or water
- Floats to confine and soak up spills on water; hugs ground for land-based spills
- Tough outer mesh is UV resistant for long-term outdoor use without degradation; lets fluids easily pass through to filler material
- Rope running along length of boom withstands up to 182kg loads, adding strength for deployment and retrieval
- Spunbond polypropylene skin is UV resistant up to 12 months; meets ANSI and MIL spec standards for static decay
- Booms float at surface for easy retrieval, even when saturated
- Absorbs and retains oils and oil-based liquids including lubricants and fuels - without taking in a drop of water
- Strong, zinc-plated carbon steel attachment clips and rings allow you to link booms together for greater length
- Bright white colour makes booms easier to see in outdoor environments and clearly shows saturation level
- Can be incinerated after use to reduce waste or for fuels blending
- When sea-weather condition is wind speed >5 knots &a (perpendicular) water-current speed >2 knots, this can cause oil absorbent booms to submerge, allowing oil to pass over them
- Waves higher than freeboard (above water) portion of boom will push oil over absorbent booms; optimal sea-weather condition for usage is typically Beafort Scale #2 or less



Specifications

| Colour | White |
|-----------------|---------------------------------|
| Dimensions | ext. dia. 13cm x 6m L |
| Fluids Absorbed | Oil-Based Liquids But Not Water |

| Recycled Content | 98% Pre-Consumer Recycled Polypropylene Filler |
|------------------|--|
| Absorbency | Up to 90.8 L per bag |
| Sold as | 2 booms per bag |
| Weight | 9.7 kg |
| # per Pallet | 12 |
| | Polypropylene Sleeve & Filler; |
| Composition | Polyester Netting; |
| | Plated Steel Rings & Clips |

Technical Information

Certifications, Approvals and Ratings ANSI/ESD STM11.11, MIL-STD-3010C Technical Documents Storage & Shelf Life of PIG Absorbents & Absorbent Spill Kits Technical Data Sheet for PIG® Oil-Only Absorbents Instructions for PIG Oil-Only Absorbent Booms Environmental Protection Act 1990 The Control of Pollution Act (1974) Water Resources Act 1991



Hogs Hill • Watt Place • Hamilton International Technology Park • Blantyre • Glasgow • G72 0AH 0800 919 900 • newpig.co.uk • pigpen@newpig.com