







PIG® Oil Pipe Leak Diverter Bucket Kit with Absorbents

TLS707 46cm x 46cm

Prevent damage to your property and equipment with a portable kit that contains all the supplies you need for diverting non-flammable oil pipe leaks.

– Hangs from a leaking pipe or other overhead oil system to catch leaks and channel them to a bucket (included)
– Vinyl-coated tarp resists punctures, UV and mildew
– Built-in grommets and included rubber straps make it easy to hang
– Bucket has a removable plug to allow the drainage hose to be inserted without having to remove the lid
– Pre-installed quick connect set lets you attach hose to leak diverter in seconds
– For use with high viscosity, non-flammable oils - flow rate of 1.5 lpm with a 1/2" ID hose (included)
– For use with low to medium viscosity, non-flammable oils - flow rate of 3.8 lpm with a 1/2" ID hose (included)
– Included absorbents and wipes soak up small oil spills
– Printed "Caution" message on bucket for added safety

Use With	Pipes
Drainage Hose	Included
Hanging Straps	Included
Corner Style	N/A
Additional Grommets per Side	N/A
Total Grommets/D-Rings	4 Grommets
Installation Method	Hanging Straps
Style	Cone
Colour	Grey

Dimensions	ext. dia. 46cm x 46cm H
Hose Connector	.75" w/ Quick Connect
Sold as	1 each
Weight	4.6 kg
# per Pallet	42
Composition	18oz PVC/Polyester with Rubber Straps, PVC Hose, Plastic Bucket, Polypropylene Mats
Flow Rate	3.8 ltr. per Minute
Includes	1 - 46cm Dia x 46cm H Leak Diverter (TLS248-GY) 4 - 36cm L Rubber Hanging Straps (TLS470) 1 - 762cm L Hose (TLS679) 1 - Hose Quick Connect (TLS680) 10 - 38cm x 51cm PIG® Oil-Only Absorbent Mat Pad (MAT423) 75 - Wipes 1 - 24.6-ltrs Bucket (TLSE155)

Technical Documents

Storage & Shelf Life of PIG Absorbents & Absorbent Spill Kits

Technical Data Sheet for PIG® Oil-Only Absorbents

Disclaimers

Nominal Dimensions

Dimensions are nominal size due to pinched corners and reinforced side walls.

Maximum Working Temperature

Not suitable for temperatures over 170°F/77°C.