


## PIG® Oil Pipe Leak Diverter Bucket Kit with Absorbents

TLS707 46cm x 46cm

Prevent damage to your property and equipment with a portable kit that contains all the supplies you need for diverting non-flammable oil pipe leaks.

- Hangs from a leaking pipe or other overhead oil system to catch leaks and channel them to a bucket (included)
- Vinyl-coated tarp resists punctures, UV and mildew
- Built-in grommets and included rubber straps make it easy to hang
- Bucket has a removable plug to allow the drainage hose to be inserted without having to remove the lid
- Pre-installed quick connect set lets you attach hose to leak diverter in seconds
- For use with high viscosity, non-flammable oils - flow rate of 1.5 lpm with a 1/2" ID hose (included)
- For use with low to medium viscosity, non-flammable oils - flow rate of 3.8 lpm with a 1/2" ID hose (included)
- Included absorbents and wipes soak up small oil spills
- Printed "Caution" message on bucket for added safety



<b>Use With</b>	Pipes
<b>Drainage Hose</b>	Included
<b>Hanging Straps</b>	Included
<b>Corner Style</b>	N/A
<b>Additional Grommets per Side</b>	N/A
<b>Total Grommets/D-Rings</b>	4 Grommets
<b>Installation Method</b>	Hanging Straps
<b>Style</b>	Cone
<b>Colour</b>	Grey

<b>Dimensions</b>	ext. dia. 46cm x 46cm H
<b>Hose Connector</b>	.75" w/ Quick Connect
<b>Sold as</b>	1 each
<b>Weight</b>	4.6 kg
<b># per Pallet</b>	42
<b>Composition</b>	18oz PVC/Polyester with Rubber Straps, PVC Hose, Plastic Bucket, Polypropylene Mats
<b>Flow Rate</b>	3.8 ltr. per Minute
<b>Includes</b>	<ul style="list-style-type: none"> <li>1 - 46cm Dia x 46cm H Leak Diverter (TLS248-GY)</li> <li>4 - 36cm L Rubber Hanging Straps (TLS470)</li> <li>1 - 762cm L Hose (TLS679)</li> <li>1 - Hose Quick Connect (TLS680)</li> <li>10 - 38cm x 51cm PIG® Oil-Only Absorbent Mat Pad (MAT423)</li> <li>75 - Wipes</li> <li>1 - 24.6-ltrs Bucket (TLSE155)</li> </ul>

## Technical Documents

[Storage & Shelf Life of PIG Absorbents & Absorbent Spill Kits](#)

[Technical Data Sheet for PIG® Oil-Only Absorbents](#)

## Disclaimers

### Nominal Dimensions

Dimensions are nominal size due to pinched corners and reinforced side walls.

### Maximum Working Temperature

Not suitable for temperatures over 170°F/77°C.



Hogs Hill • Watt Place • Hamilton International Technology Park • Blantyre • Glasgow • G72 0AH  
0800 919 900 • [newpig.co.uk](http://newpig.co.uk) • [pigpen@newpig.com](mailto:pigpen@newpig.com)