

PIG® Original SpillBlocker® Dike

PLRE204 10cm x 3m x 6cm, Polyurethane, 1 each

Prevent spills from reaching drains or valuable stock with this reusable barrier!

- Portable barrier forms a tight seal on smooth surfaces and is flexible enough to conform to irregular curves — diverts liquids away from drains and protects inventory and supplies
- Improved 2 layer construction resists rips and tears
- Resists water, oil and most chemicals
- Reusable — cleans easily with soap and water
- Made of flexible, non-absorbent polyurethane
- Create any shape or configuration — even join Dikes together with optional Corners and Connectors
- Available in high-visibility yellow or grime-hiding black
- 1 Barrier (6cm H x 10cm W x 3m L)



Item#	Description	Dimensions	Weight
PLRE204-YW	Yellow	10cm W x 3m L x 6cm H	13.43 kg
PLRE204-BK	Black	10cm W x 3m L x 6cm H	13.43 kg

Metric Equivalent:

Item#	Description	Dimensions	Weight
PLRE204-YW	Yellow		
PLRE204-BK	Black		

Specifications

Style	Non-Weight Bearing
Dimensions	10cm W x 3m L x 6cm H
Intended For	Use on Smooth Surface
Max liquid temp exposure	Max Exposure Limit 107°C (225°F) for up to 30 Minutes
Storage Temp Range	Store from -18°C (0°F) to 49°C (120°F)
Temperature Limit	Works from -18°C (0°F) to 71°C (160°F) up to 12 months
Sold as	1 each

Weight	13.43 kg
# per Pallet	56
Composition	Polyurethane

Technical Documents

[PIG SpillBlocker Dikes, DrainBlocker Drain Covers and other Blockers](#)

[Instructions for PIG Original SpillBlocker Dike](#)

[Technical Data Sheet for PIG® Blocker Products](#)

[Urethane Use, Care and Storage](#)

[Environmental Protection Act 1990](#)

[Water Resources Act 1991](#)

Disclaimers

Urethane Notice

Due to the nature of softer urethane, the physical properties of these products may change over time with exposure to certain environmental conditions like temperature, humidity and UV radiation. Typical life expectancy is 5 years. Please inspect the stored product regularly to ensure it is in a usable state. For optimum performance, ensure that the area where the product will be deployed is free of debris, cracks and holes. For more details and for chemical compatibility, please call Technical Services.



Hogs Hill • Watt Place • Hamilton International Technology Park • Blantyre • Glasgow • G72 0AH
0800 919 900 • newpig.co.uk • pigpen@newpig.com