



## PIG® Pipe Filter Sock

FLT940 For 5cm to 10cm Dia. Pipes, Holds 4 ltrs., 1 each

Filter water during lower-volume pump-outs or from discharge pipes using this pipe filter sock that captures sediment and absorbs oil.

- Ideal for pumping out lower-volume containment areas, collection ponds, utility vaults and sumps, or for use on discharge pipes
- Simply attach to hose or pipe to remove hydrocarbons and sediment from pumped water
- Included hose clamp threads through precut openings



<b>Substance Filtered</b>	Oil; Fuels; Sediment; Floatables; Debris
<b>Use With</b>	5cm to 10cm Dia. Pipes
<b>Colour</b>	Black
<b>Dimensions</b>	ext. dia. 10cm x 152cm L
<b>Absorbency</b>	Up to 4 L
<b>Micron Rating</b>	74 Microns
<b>Sold as</b>	1 each
<b>Weight</b>	.79 kg
<b># per Pallet</b>	300
<b>Composition</b>	Pipe Sock - Polyester; Hose Clamp - Stainless Steel
<b>Capacity</b>	4 ltrs.
<b>Maximum Flow Rate</b>	1,023 ltr./Minute

### Technical Documents

[Instructions for PIG Pipe Filter Sock](#)

[Product Performance and Testing for PIG Pipe Filter Sock](#)

### Disclaimers

## Oil Filter Notice

Liquid should always be checked before discharge into the environment.



Hogs Hill • Watt Place • Hamilton International Technology Park • Blantyre • Glasgow • G72 0AH

0800 919 900 • [newpig.co.uk](http://newpig.co.uk) • [pigpen@newpig.com](mailto:pigpen@newpig.com)