







PIG® Pipe Filter Sock

FLT941 For 13cm to 20cm Dia. Pipes, Holds 6.8 ltrs., 1 each

Filter water during lower-volume pump-outs or from discharge pipes using this pipe filter sock that captures sediment and absorbs oil.

- Ideal for pumping out lower-volume containment areas, collection ponds, utility vaults and sumps, or for use on discharge pipes
- Simply attach to hose or pipe to remove hydrocarbons and sediment from pumped water
- Included hose clamp threads through precut openings

Substance Filtered	Oil; Fuels; Sediment; Floatables; Debris
Use With	13cm to 20cm Dia. Pipes
Colour	Black
Dimensions	ext. dia. 20cm x 152cm L
Absorbency	Up to 6.8 L
Micron Rating	74 Microns
Sold as	1 each
Weight	1.25 kg
# per Pallet	80
Composition	Pipe Sock - Polyester; Hose Clamp - Stainless Steel
Capacity	6.8 ltrs.
Maximum Flow Rate	1,705 ltr./Minute

Technical Documents

Instructions for PIG Pipe Filter Sock

Product Performance and Testing for PIG Pipe Filter Sock

Disclaimers

Oil Filter Notice

Liquid should always be checked before discharge into the environment.

New Pig
World's best stuff for leaks, drips and spills.

Hogs Hill • Watt Place • Hamilton International Technology Park • Blantyre • Glasgow • G72 0AH
0800 919 900 • newpig.co.uk • pigpen@newpig.com