

PIG® Pipe Repair Tape

PTYE121-1 For 100mm to 200mm Dia.
Pressurised Pipes & Joints (up to 10 bar/150 psi), 1
each

Instantly repair those small, unexpected pipe leaks in your low-pressure system with our Pipe Repair Tape! It seals in minutes and can be used without relieving pipe pressure, so you keep your facility dry, safe and operational.

- One-part tape allows immediate and economical repairs to low-pressure systems without shutting down; keep on site to rapidly seal pipe ruptures
- Little to no surface preparation needed; bonds to copper, steel, PVC and more
- Seals effectively after only 5 minutes and cures completely after only 30 minutes
- Simple to use; just soak in water and wrap around leak areas
- Applications include petrochemical, manufacturing, food and chemical processing
- Cured wrap can be sanded and painted
- Wrap a minimum of 10-12 times around the pipe for maximum service creating a layer of approximately 12mm; each wrap can repair a pipe 100mm to 200mm in diameter
- Repair a maximum pipeline pressure of 27.5 bar (400psi) by using 2 complete wraps



Use With	100mm to 200mm Dia. Pressurised Pipes & Joints (up to 10 bar/150 psi)
Colour	Natural
Dimensions	5cm W x 3.6m L
Cure Time	30 Minutes
Temperature Limit	150°C (302°F) Continuous
Sold as	1 each
Weight	0.15 kg
Composition	Woven polyester fabric with polyurethane resin

Certifications, Approvals and Ratings

BS 6920 Suitable for use with water intended for human consumption.

Technical Documents

Pipe Repair Tape

Pipe Repair Tape



New Pig

World's best stuff for leaks, drips and spills.

Hogs Hill • Watt Place • Hamilton International Technology Park • Blantyre • Glasgow • G72 0AH

0800 919 900 • newpig.co.uk • pigpen@newpig.com