

PIG® PLUG-N-SEAL® Patching Paste

PTY220 For Fuel Tanks, Steel Drums & Containers, 1 - 454g Container

Even in cold temperatures, our ready-to-use paste instantly stops leaks for up to 2 hours.

- Temporarily stops leaks - even in cold temperatures - until system can be drained or leak source contained
- Bentonite Glycol mix provides excellent chemical resistance for fuel leaks; not recommended for plugging containers of antifreeze, acids, caustics, or oxidisers
- No preparation needed, even on dirty or rusty surfaces
- Temporarily stops leaks from 2 minutes up to 2 hours
- Ready to use without mixing

Use With	Fuel Tanks, Steel Drums & Containers
Colour	Grey
Dimensions	ext. dia. 9cm x 7cm H
Temperature Limit	0°C (32°F) to 66°C (150°F)
Sold as	1 each
Weight	0.45 kg
Composition	Bentonite Clay & Water w/ Polymer Base
Shelf Life	2 years
Volume	454g Container

Technical Documents

Technical Data Sheet for PIG® Plug-N-Seal™ Patching Paste

New Pig
World's best stuff for leaks, drips and spills.

Hogs Hill • Watt Place • Hamilton International Technology Park • Blantyre • Glasgow • G72 0AH
0800 919 900 • newpig.co.uk • pigpen@newpig.com