



PIG® Round Oil Containment Boom

BOME221 20cm Freeboard, 55cm Draft, 6000kg Break Strength

A light weight floating boom used to contain and control the spread of debris and waterborne spills such as oil and fuel. Used for fast response and preventative deployment in easy water such as harbours, rivers, lakes and coastal waters close to shore.

- The PIG® Round Oil Containment Boom is light weight and easy to handle; no need to use boats or cranes
- Easily stored and transported
- Suitable for use in easy waters such as harbours, rivers and lakes and on coastal waters close to the shore. Not recommended for use on open sea
- The PIG® Round Oil Containment Boom is very flexible, allowing the product to adapt and adjust to the flow of the water, waves and currents
- PVC material is strong and durable and has a smooth surface finish, making it easy to decontaminate after use
- Strong, aluminium ASTM couplings allow multiple units to be easily and securely linked together
- Floats in the PIG® Round Oil Containment Boom are stable and round, which makes the boom more stable in the water than a flat one
- The PIG® Round Oil Containment Boom floats are round, which prevents the boom from "sticking" to itself during deployment, making response fast and easy
- Floats are constructed of closed-cell foam, ensuring they stay water-repellent indefinitely during use
- Standard booms use galvanised chain which is ideal for freshwater deployment, and will resist corrosion for up to 6-months of continuous deployment in sea water

NOTE: Not recommended for use in open seas.



Item#	Description	Dimensions	Weight
-------	-------------	------------	--------

BOME221

1m L x 75cm H

3 kg

Metric Equivalent:

Item#	Description	Dimensions	Weight
-------	-------------	------------	--------

BOME221

Specifications

Dimensions	1m L x 75cm H
Maximum Order Length	25
Minimum Order Length	1
Maximum Section Length	25m
Sold as	1 metre
Weight	3 kg
Composition	900g PVC with galvanised steel chain and ASTM spec aluminium coupling
Break Strength	6000kg
Draft Dimensions	55cm
Freeboard Dimensions	20cm

Technical Documents

[Environmental Protection Act 1990](#)[The Control of Pollution Act \(1974\)](#)[Water Resources Act 1991](#)

Disclaimers

[Containment Boom - Open Sea Notice](#)

Not recommended for use in open seas.

**New Pig**

World's best stuff for leaks, drips and spills.

Hogs Hill • Watt Place • Hamilton International Technology Park • Blantyre • Glasgow • G72 0AH

0800 919 900 • newpig.co.uk • pigpen@newpig.com