



PIG® Grippy® Adhesive-Backed Antimicrobial Floor Mats for Sinks & Dryers - Large

GRP7007 61cm x 89cm, 4 pads, Absorbs up to 2.34 L per box

Keep restroom floors dry and safe when people wash their hands with our adhesive-backed mats. Absorbent top soaks up water and other liquids.

- Sink & Dryer Mats capture water to keep floors dry in front of sinks and under hand dryers and towel dispensers; also help control slip hazards around drinking fountains, showers, and other wet trouble spots
- Permanently infused antimicrobial technology prevents the growth of odour-causing bacteria and mould on the mats to keep restrooms cleaner and fresher smelling
- Proprietary, full-coverage adhesive backing keeps mats in place underfoot with no shifting, curling or flipping up to stop slip and trip hazards; peels up easily
- Mats stick to your floor and won't budge while you clean them; simply mop them with the rest of the floor
- Durable, surface stands up to daily cleaning and foot traffic
- Absorbent top layer captures water on contact, wicks it away and dries out quickly
- Impermeable backing layers stop liquid pass-through to prevent stains and grout damage
- PIG Grippy Floor Mat has a 91% lower environmental impact than rental floor mats (Please contact us for further details regarding the Life Cycle Assessment report.)
- PIG Grippy Floor Mat classified as slip resistance R13 according to DIN51130 - suitable for use on floors in workrooms and work areas where there is an increased risk of slipping due to grease, oil, water, foods, left-overs, dust, flour, plant clippings, etc.
- Tested in accordance with BS 7976-2:2002+A1:2013, and demonstrated low slip potential in both wet and dry conditions
- Fire classification Bfl-s1 when tested according to BS EN 13501-1
- Tested and Certified by the National Floor Safety Institute (NFSI): when used as part of your floor safety program, high-traction surfaces such as PIG Grippy Floor Mat have been

proven to reduce slip-and-fall claims by as much as 90%

- Release paper on the bottom of the mat should be removed prior to installation
- Mats take on the properties of absorbed liquids
- always take proper precautions when handling saturated absorbents



Item#	Description	Dimensions	Weight
GRP7007-BK	Black	61cm W x 89cm L	1.8 kg

Metric Equivalent:

Item#	Description	Dimensions	Weight
GRP7007-BK	Black		

Specifications

Storage Temperature	Store between 0°C - 49°C
Dimensions	61cm W x 89cm L
Mat Weight	Mediumweight
Fluids Absorbed	Water; Grease; Oils
Absorbency	Up to 2.34 L per box
Perforated	Not perforated
Temperature Limit	Surface temperatures from 13°C - 49°C
Sold as	4 pads per box
Weight	1.8 kg
# per Pallet	228
Composition	Absorbent - Polypropylene; Adhesive Backing - Proprietary Adhesive Material
Packaging	Box
Poly-Backing	Poly-Backed
UV Resistant	UV Resistant

Technical Information

Certifications, Approvals and Ratings

NSFI Certified,ANSI B101.1- 2009,DIN 51130:2014 - R13,BS 7976-2:2002+A1:2103 - Low slip,BS EN 13501-1:2007+A1:2009 - Bfl-s1,Tested in accordance with BS EN ISO 9239-1:2010,Tested in accordance with BS EN ISO 11925-2:2010,ASTM G154-1 (Black & Grey only)

Technical Documents

[PIG Grippy Adhesive-Backed Mat](#)

[Storage & Shelf Life of PIG Absorbents & Absorbent Spill Kits](#)

[Technical Data Sheet for PIG® Adhesive Backed Grippy Mat](#)

[Instructions for PIG Grippy Floor Mat](#)

[Grippy Increased Service Life Report](#)

[PIG® Grippy® Adhesive-Backed Floor Mat Scrubber Guidelines](#)

Disclaimers

PIG® Grippy® Floor Mat Notice

New Pig adhesive-backed mats are formulated to work with most common industrial and commercial floor surfaces but are not intended for home/residential use and wood flooring. All adhesive mats have some potential to leave residue or lift or discolour finish coatings, paint, and loose or pre-damaged tiles depending on the condition and age of the floor surface. If you have questions about the suitability of New Pig adhesive-backed mats for your application, test a 15 x 15cm piece in a non-critical area before use.

PIG® Grippy® Floor Mats should be replaced if they show signs of wear or damage and should always be changed out every 3 to 6 months, depending on conditions and traffic patterns.

Customer assumes the risk that a New Pig adhesive-backed mat may damage or alter their existing flooring or floor covering. Other than warranties implied by law, New Pig provides no warranty of fitness for a particular purpose and no warranty that an adhesive-backed mat will be fit for customer's intended use. Other than in respect of liability which New Pig cannot lawfully exclude, New Pig shall have no responsibility for, and customer hereby releases and discharges New Pig from, any direct, indirect, incidental or consequential damages to their floors, flooring material, or any other surfaces in their premises. Customer is solely responsible for determining the fitness and appropriateness of the use of New Pig adhesive-backed mats in their premises.



Hogs Hill • Watt Place • Hamilton International Technology Park • Blantyre • Glasgow • G72 0AH
0800 919 900 • newpig.co.uk • pigpen@newpig.com