

PIG® SPILLBLOCKER® Dike

PLR230 5cm x 3m x 6cm, Polyurethane, 1 each

Spills on asphalt can seep underneath standard spill dikes. Stop them in their tracks with our Rough Surface Dike!

- Exclusive New Pig formulation features a tear-resistant top layer with a super-tacky bottom layer that seals tight to rough surfaces and blocks liquids
- Bottom layer "seeps" into surface cracks to form a liquid-tight seal
- Fast protection for when a spill is heading right for your drain on a rough surface; just set dike down with sticky side away from surface, turn dike over and press into place
- Confines and diverts fluids without absorbing them, making cleanup or reclamation simpler
- 6cm height contains spills up to 5cm deep
- Polyurethane material resists water, oils and many chemicals
- High-visibility yellow top colour draws attention to spill for increased safety
- Connector piece included to create a liquid-proof seal and allow you to join as many sections as needed
- Light-weight dike is easy to handle and deploy
- Intended for one-time, limited term use; ideal for containing hazardous or other liquids on rough surfaces



Specifications

Style	Non-Weight Bearing
Colour	Yellow/Black
Dimensions	5cm W x 3m L x 6cm H
Intended For	Use on Rough Surface
Max liquid temp exposure	Max Exposure Limit 107°C (225°F) for up to 30 Minutes
Storage Temp Range	Store from -18°C (0°F) to 49°C (120°F)
Temperature Limit	Works from -18°C (0°F) to 71°C (160°F) up to 12 months
Sold as	1 each
Weight	5.9 kg
# per Pallet	28

Composition	Polyurethane
Includes	1 - Connector 1 - Yellow Disposal Bag

Technical Documents

[PIG SpillBlocker Dikes, DrainBlocker Drain Covers and other Blockers](#)

[Urethane Use, Care and Storage](#)

[Technical Data Sheet for PIG® Blocker Products](#)

[Environmental Protection Act 1990](#)

[Water Resources Act 1991](#)

Disclaimers

Urethane Notice

Due to the nature of softer urethane, the physical properties of these products may change over time with exposure to certain environmental conditions like temperature, humidity and UV radiation. Typical life expectancy is 5 years. Please inspect the stored product regularly to ensure it is in a usable state. For optimum performance, ensure that the area where the product will be deployed is free of debris, cracks and holes. For more details and for chemical compatibility, please call Technical Services.



Hogs Hill • Watt Place • Hamilton International Technology Park • Blantyre • Glasgow • G72 0AH
0800 919 900 • newpig.co.uk • pigpen@newpig.com