PIG® SPILLBLOCKER® Vacuum Dike







PLR280 10cm x 152cm x 6cm, Vacuum Dike - 100% Polyurethane; Outlet pipe - PVC; Vacuum reducer - Polyethylene, 1 each

Attach this unique spill dike to your wet vac system to capture and contain liquids at the same time.

- Simply place the dike on the floor and connect it to your wet/dry vacuum
- Four intakes and integrated vacuum channels suck up liquid quicker than a traditional vacuum head
- Ideal for spill response or to contain and capture liquid during routine washdowns
- PVC outlet pipe attaches to most wet vacuum hoses; includes two reducing couplers to fit 1.5" and 2.25" hoses
- Connects to any 6cm H SpillBlocker Dike (connector sold separately) to create larger containment area
- Reusable dike cleans easily with soap and water
- Polyurethane construction resists water, oils and many chemicals

Item#	Description	Dimensions	Weight
PLR280-BK	Black	10cm W x 152cm L x 6cm H	6.5 kg

Item#	Description	Dimensions	Weight
PLR280-BK	Black		

Style	Non-Weight Bearing
Dimensions	10cm W x 152cm L x 6cm H
Intended For	Use on Smooth Surface
Max liquid temp exposure	Max Exposure Limit 107°C (225°F) for up to 30 Minutes
Storage Temp Range	Store from -18°C (0°F) to 49°C (120°F)
Temperature Limit	Works from -18°C (0°F) to 71°C (160°F) up to 12 months
Sold as	1 each
Weight	6.5 kg

New Pig Patent	5,236,281
# per Pallet	72
Composition	Vacuum Dike - 100% Polyurethane; Outlet pipe - PVC; Vacuum reducer - Polyethylene

Technical Documents

PIG SpillBlocker Dikes, DrainBlocker Drain Covers and other Blockers

Urethane Use, Care and Storage

Technical Data Sheet for PIG® Blocker Products

Instructions for PIG SpillBlocker® Vacuum Dike

Disclaimers

Urethane Notice

Due to the nature of softer urethane, the physical properties of these products may change over time with exposure to certain environmental conditions like temperature, humidity and UV radiation. Typical life expectancy is 5 years. Please inspect the stored product regularly to ensure it is in a usable state. For optimum performance, ensure that the area where the product will be deployed is free of debris, cracks and holes. For more details and for chemical compatibility, please call Technical Services.

New Pig
World's best stuff for leaks, drips and spills.

Hogs Hill • Watt Place • Hamilton International Technology Park • Blantyre • Glasgow • G72 0AH
0800 919 900 • newpig.co.uk • pigpen@newpig.com