

## PIG® SPILLBLOCKER® Vacuum Dike

PLR280 10cm x 152cm x 6cm, Vacuum Dike - 100% Polyurethane; Outlet pipe - PVC; Vacuum reducer - Polyethylene, 1 each

Attach this unique spill dike to your wet vac system to capture and contain liquids at the same time.

- Simply place the dike on the floor and connect it to your wet/dry vacuum
- Four intakes and integrated vacuum channels suck up liquid quicker than a traditional vacuum head
- Ideal for spill response or to contain and capture liquid during routine washdowns
- PVC outlet pipe attaches to most wet vacuum hoses; includes two reducing couplers to fit 1.5" and 2.25" hoses
- Connects to any 6cm H SpillBlocker Dike (connector sold separately) to create larger containment area
- Reusable dike cleans easily with soap and water
- Polyurethane construction resists water, oils and many chemicals



Item#	Description	Dimensions	Weight
PLR280-BK	Black	10cm W x 152cm L x 6cm H	6.5 kg

Item#	Description	Dimensions	Weight
PLR280-BK	Black		

<b>Style</b>	Non-Weight Bearing
<b>Dimensions</b>	10cm W x 152cm L x 6cm H
<b>Intended For</b>	Use on Smooth Surface
<b>Max liquid temp exposure</b>	Max Exposure Limit 107°C (225°F) for up to 30 Minutes
<b>Storage Temp Range</b>	Store from -18°C (0°F) to 49°C (120°F)
<b>Temperature Limit</b>	Works from -18°C (0°F) to 71°C (160°F) up to 12 months
<b>Sold as</b>	1 each
<b>Weight</b>	6.5 kg

**New Pig Patent**

5,236,281

**# per Pallet**

72

**Composition**

Vacuum Dike - 100% Polyurethane;  
Outlet pipe - PVC;  
Vacuum reducer - Polyethylene

## Technical Documents

[PIG SpillBlocker Dikes, DrainBlocker Drain Covers and other Blockers](#)

[Urethane Use, Care and Storage](#)

[Technical Data Sheet for PIG® Blocker Products](#)

[Instructions for PIG SpillBlocker® Vacuum Dike](#)

## Disclaimers

[Urethane Notice](#)

Due to the nature of softer urethane, the physical properties of these products may change over time with exposure to certain environmental conditions like temperature, humidity and UV radiation. Typical life expectancy is 5 years. Please inspect the stored product regularly to ensure it is in a usable state. For optimum performance, ensure that the area where the product will be deployed is free of debris, cracks and holes. For more details and for chemical compatibility, please call Technical Services.



Hogs Hill • Watt Place • Hamilton International Technology Park • Blantyre • Glasgow • G72 0AH  
0800 919 900 • [newpig.co.uk](http://newpig.co.uk) • [pigpen@newpig.com](mailto:pigpen@newpig.com)