













TLS753 86cm x 132cm

Go from storage bag to fully functioning leak diverter in less than two minutes!

- Coiled diverter springs open for hassle-free installation in under two minutes
- Rigid outer rim holds diverter open for easy handling
- Straps, hooks and clamps can be adjusted in seconds; just nudge your diverter until it's centered and leveled, even if hanging points are uneven
- All diverter components are pre-attached for speedy setup; flexible PVC drainage hose (included) clicks into place with pre-installed quick-connect adapter
- Hangs easily in problem spots to catch nuisance leaks and channel them to a floor drain or collection container
- Non-permeable tarp is vinyl coated for strength and durability; resists punctures, UV and mildew for long product life
- Conical shape helps funnel liquid toward center for better drainage; clear colour helps monitor debris and liquid flow
- Flow rate of 12.6ltrs per minute when used with supplied 1/2" ID hose
- Ready-to-use right out of the convenient storage bag





| Item# | Description | Dimensions | Weight | |
|--------------------|-------------|------------------|--------|--|
| TLS753-CL | Clear | 86cm W x 132cm L | 2.4 kg | |
| Metric Equivalent: | | | | |
| Item# | Description | Dimensions | Weight | |
| TLS753-CL | Clear | | | |

Specifications

| Use With | Pipes & Roofs |
|----------------|---------------|
| Drainage Hose | Included |
| Hanging Straps | Included |
| | |

Corner Style N/A

| Additional Grommets per Side | N/A | |
|------------------------------|--|--|
| Total Grommets/D-Rings | 12 Grommets | |
| Installation Method | Hanging Straps | |
| Style | Oval | |
| Dimensions | 86cm W x 132cm L | |
| Hose Connector | .75" w/ Quick Connect | |
| Sold as | 1 each | |
| Weight | 2.4 kg | |
| New Pig Patent | Patent Pending | |
| # per Pallet | 72 | |
| Composition | Diverter - PVC, Polyester; Hose - PVC; Hooks - Plastic | |
| Flow Rate | 12.6 ltr. per Minute | |
| Includes | 1 - 86cm x 132cm Leak Diverter 1 - Quick Connect (TLS680) 1 - 762cm L Drainage Hose (TLS679) 2 - Adjustable Length Bungee Cords 4 - Hanging Hooks 1 - Vinyl Storage Bag | |

Technical Documents

REACH Statement

Disclaimers

Maximum Working Temperature

Not suitable for temperatures over 170°F/77°C.



Hogs Hill • Watt Place • Hamilton International Technology Park • Blantyre • Glasgow • G72 0AH 0800 919 900 • newpig.co.uk • pigpen@newpig.com