



## **PIG® Suspended Ceiling Leak Diverter**

TLS102 123cm x 127cm

Our low-profile leak diverter clips to your drop ceiling grid to capture leaks and drips and divert them to a drain.

- Low-profile diverter hangs only centimetres away from ceiling; won't impede traffic or draw attention
- Can be installed close to the wall, in a corner or directly in the middle of any room with a drop ceiling
- Nonpermeable tarp is vinyl-coated for strength and durability; resists punctures, UV and mildew for long life
- Installs easily with four ceiling grid clips
- Internal fibreglass rods add support and prevent bowing and sagging
- Can span multiple panels depending on placement of grid clips
- Captures leaks and drips and diverts them to a drain or storage tank with the included 762cm L clear hose
- Neutral tarp colour and clear drainage hose blend in with most indoor environments
- Includes eight additional ceiling grid clips and a length of plastic chain to create the correct hose slope for water discharge

pig

## Specifications

Use With	Drop Ceilings
Drainage Hose	Included
Hanging Straps	N/A
Corner Style	Clips
Additional Grommets per Side	N/A
Total Grommets/D-Rings	N/A
Installation Method	Ceiling Clips
Style	Square
Colour	White
Dimensions	123cm W x 127cm L
Hose Connector	.25"

Sold as	1 per box
Weight	1.4 kg
# per Pallet	42
Composition	13oz PVC/Polyester, with Fibreglass Rods, and PVC Hose
Flow Rate	4 Itr. per Minute
Includes	<ol> <li>1 - 127cm L x 123cm W Leak Diverter</li> <li>2 - 9.5mm dia x 124cm L Fibreglass Rods</li> <li>2 - 9.5mm dia x 137cm L Fibreglass Rods</li> <li>1 - 6.3mm ID. x 762cm L Hose</li> <li>4 - Hook Style Ceiling Clips</li> <li>8 - Additional Ceiling Grid Clips w/ S hooks</li> </ol>

## Disclaimers

Maximum Working Temperature

Not suitable for temperatures over 170°F/77°C.



Hogs Hill • Watt Place • Hamilton International Technology Park • Blantyre • Glasgow • G72 0AH 0800 919 900 • newpig.co.uk • pigpen@newpig.com