

# PIG® Trough Style Roof Leak Diverter

TLS674 41cm x 152cm

Stop devastating roof leak damage and protect your people, equipment and inventory with the original diverter. Invented here!

- The original Leak Diverter - invented here and engineered to stop devastating roof leak damage every time, guaranteed
- Long, rectangular shape is ideal for catching leaks or accumulated condensation along cracks, fissures or pipes
- Hangs easily in problem spots to catch nuisance leaks and channel them to a floor drain or collection container
- Ideal for quick response to avoid downtime after a roof leak or for long-term prevention in leak-prone areas
- Nonpermeable tarp is vinyl coated for strength and durability; resists punctures, UV and mildew for long life
- Pinched corners help funnel liquid toward center for better drainage
- Grommets resist tearing and make installation easy
- Long and narrow 41cm tarp width offers maximum coverage for narrow spaces and fits perfectly between ceiling joists
- Edges feature rods along length for additional stability
- Accepts a standard 3/4" hose connection to channel liquid to floor drain or collection container (hose sold separately)
- Flow rate of 12.6 litres per minute when used with a 1/2" ID hose



Item#	Description	Dimensions	Weight
TLS674-TR	Translucent	41cm W x 152cm L	.75 kg

Item#	Description	Dimensions	Weight
TLS674-TR	Translucent		

<b>Use With</b>	Roofs
<b>Drainage Hose</b>	Sold separately
<b>Hanging Straps</b>	Sold separately
<b>Corner Style</b>	7.5cm Pinched Corner with Grommet
<b>Additional Grommets per Side</b>	1 per long side, 107cm spacing
<b>Total Grommets/D-Rings</b>	6 Grommets
<b>Installation Method</b>	Hanging Straps
<b>Style</b>	Trough Style
<b>Dimensions</b>	41cm W x 152cm L
<b>Hose Connector</b>	.75"
<b>Sold as</b>	1 each
<b>Weight</b>	.75 kg
<b># per Pallet</b>	90
<b>Composition</b>	13oz PVC/Polyester
<b>Flow Rate</b>	12.6 ltr. per Minute

## Technical Documents

[REACH Statement](#)

[Instructions for PIG Trough Style Roof Leak Diverter](#)

## Disclaimers

[Maximum Working Temperature](#)

Not suitable for temperatures over 170°F/77°C.

[Nominal Dimensions](#)

Dimensions are nominal size due to pinched corners and reinforced side walls.



Hogs Hill • Watt Place • Hamilton International Technology Park • Blantyre • Glasgow • G72 0AH  
0800 919 900 • [newpig.co.uk](http://newpig.co.uk) • [pigpen@newpig.com](mailto:pigpen@newpig.com)