



PIG® WashBlocker® Dike

PLR500 3cm x 3m x 1.9cm, Top Skin - Polypropylene; Bottom Layer - Polyurethane, 1 each

Easily keep washdown liquid from reaching neighboring areas or carpeted floors.

- Use low-profile spill dike for routine containment of washdown and sanitising liquid
- Block doorways, protect carpeting, and channel liquid to drains
- Tacky urethane construction creates a leakproof seal on dry floors
- Tear-resistant polypropylene top withstands repeated use
- Lightweight strip is easy to handle and store
- Reusable barrier cleans up with soap and water
- Bright-green colour is highly visible

Specifications

Style	Non-Weight Bearing
Colour	Hi-vis Green
Dimensions	3cm W x 3m L x 1.9cm H
Intended For	Use on Smooth Surface
Max liquid temp exposure	Max Exposure Limit 107°C (225°F) for up to 30 Minutes
Storage Temp Range	Store from -18°C (0°F) to 49°C (120°F)
Temperature Limit	Works from -18°C (0°F) to 71°C (160°F) up to 12 months
Sold as	1 per box
Weight	1.18 kg
New Pig Patent	Patent Pending, Patent 5,236,281
# per Pallet	324
Composition	Top Skin - Polypropylene; Bottom Layer - Polyurethane

Technical Documents

[PIG® Washblocker Strip](#)

[Technical Data Sheet for PIG® Blocker Products](#)

[Urethane Use, Care and Storage](#)

Disclaimers

Urethane Notice

Due to the nature of softer urethane, the physical properties of these products may change over time with exposure to certain environmental conditions like temperature, humidity and UV radiation. Typical life expectancy is 5 years. Please inspect the stored product regularly to ensure it is in a usable state. For optimum performance, ensure that the area where the product will be deployed is free of debris, cracks and holes. For more details and for chemical compatibility, please call Technical Services.



New Pig

World's best stuff for leaks, drips and spills.

Hogs Hill • Watt Place • Hamilton International Technology Park • Blantyre • Glasgow • G72 0AH

0800 919 900 • newpig.co.uk • pigpen@newpig.com